

Product type designation
Product description

Antenna cable for HF, TNC / TNC
Coaxial cable
MOBY D Antenna connection cable for ANT D5, ANT D6 and ANT D10 between antenna and SLG D10/SLG D10S or RF290 Antenna switch, IP65, PVC, Length 3.3 m



Figure similar

Suitability for use	Plug-in cable for connecting a long-range HF antenna to a reader via TNC connector
Cable designation	RG58 C/U
Wire length	3.3 m
Electrical data	
Number of electrical connections	2
Type of electrical connection	TNC (male, straight) / TNC / (male, straight)
Impedance	
• Rated value	50 Ω
Loop resistance per length / maximum	53 mΩ/m
Operating voltage	
• maximum	1400 V
Mechanical data	
Design of the shield	CuG tin-plated
Outer diameter	
• of cable sheath	4.85 mm

Material	
• of dielectric	PE
• of cable sheath	PVC
Color	
• of cable sheath	Black
Bending radius	
• with single bend / minimum permissible	25 mm
Weight per length	36 kg/km

Permitted ambient conditions

Ambient temperature	
• during operation	-35 ... +80 °C
• during storage	-35 ... +80 °C
• during transport	-35 ... +80 °C
• during installation	-35 ... +80 °C

Standards, specifications, approvals

UL/ETL listing / 300 V Rating	No
-------------------------------	----

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL	https://support.industry.siemens.com/cs/ww/en/view/67384964
• to website: Industrial communication	http://www.siemens.com/ident/rfid
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAX Download Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified: 05/16/2018