

SIMATIC ET 200AL, DIQ 16x24 V DC/0.5 A, 8xM12, Degree of protection IP67



General information	
Product type designation	DIQ 16X24VDC/0.5A, 8XM12
HW functional status	E01
Firmware version	V1.1.x
Product function	
• I&M data	Yes; I&M0 to I&M3
Engineering with	
• STEP 7 TIA Portal configurable/integrated as of version	STEP 7 V14 or higher
• STEP 7 configurable/integrated as of version	V5.5 SP4 Hotfix 7 or higher
• PROFIBUS as of GSD version/GSD revision	GSD as of Revision 5
• PROFINET as of GSD version/GSD revision	GSDML V2.3.1
Operating mode	
• DI	Yes
• Counter	Yes
• DQ	Yes
Supply voltage	
Load voltage 1L+	

• Rated value (DC) • permissible range, lower limit (DC) • permissible range, upper limit (DC) • Reverse polarity protection	24 V 20.4 V 28.8 V Yes; Against destruction; encoder power supply outputs applied with reversed polarity, loads pick up
Load voltage 2L+	
• Rated value (DC) • permissible range, lower limit (DC) • permissible range, upper limit (DC) • Reverse polarity protection	24 V 20.4 V 28.8 V Yes; Against destruction; encoder power supply outputs applied with reversed polarity, loads pick up
Input current	
Current consumption (rated value)	75 mA; without load
from load voltage 1L+ (unswitched voltage)	4 A; Maximum value
from load voltage 2L+, max.	4 A; Maximum value
Encoder supply	
Number of outputs	8
24 V encoder supply	
• Short-circuit protection • Output current, max.	Yes; Per load voltage, electronic 1.4 A; Total current of all encoders, max. 0.7 A per load voltage
Power loss	
Power loss, typ.	4 W
Digital inputs	
Number of digital inputs	16; Parameterizable as DIQ
Input characteristic curve in accordance with IEC 61131, type 3	Yes
Number of simultaneously controllable inputs	
all mounting positions	
— up to 55 °C, max.	16
Digital input functions, parameterizable	
• Freely usable digital input • Counter — Number, max. — Counting frequency, max. — Counting width — Counting direction up/down	Yes Yes 4 2 kHz 32 bit; Incl. sign Yes
Input voltage	
• Type of input voltage • Rated value (DC) • for signal "0" • for signal "1"	DC 24 V -3 to +5V +11 to +30V

Input current	
• for signal "1", typ.	3 mA
Input delay (for rated value of input voltage)	
for standard inputs	
— parameterizable	Yes
— at "0" to "1", min.	0.05 ms; 1.6 ms for channels 8 through 15
— at "0" to "1", max.	20 ms
— at "1" to "0", min.	0.05 ms; 1.6 ms for channels 8 through 15
— at "1" to "0", max.	20 ms
for technological functions	
— parameterizable	Yes
Cable length	
• unshielded, max.	30 m
Digital outputs	
Number of digital outputs	16; Parameterizable as DIQ
• in groups of	8; 2 load groups for 8 outputs each
Short-circuit protection	Yes; per channel, electronic
• Response threshold, typ.	0.7 A
Limitation of inductive shutdown voltage to	L+ (-53 V)
Digital output functions, parameterizable	
• Switching tripped by comparison values	Yes
• Freely usable digital output	Yes
Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	4 k Ω
Output voltage	
• for signal "1", min.	L+ (-0.8 V)
Output current	
• for signal "1" rated value	0.5 A
• for signal "0" residual current, max.	0.5 mA
Switching frequency	
• with resistive load, max.	100 Hz
• with inductive load, max.	0.5 Hz
• on lamp load, max.	1 Hz
Total current of the outputs	
• Current per group, max.	4 A
Cable length	
• unshielded, max.	30 m
Encoder	

Connectable encoders	
• 2-wire sensor	Yes
— permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Substitute values connectable	Yes; channel by channel, parameterizable
Alarms	
• Diagnostic alarm	Yes; Parameterizable
Diagnostic messages	
• Short-circuit	Yes; Outputs to M; encoder supply to M; module by module
Diagnostics indication LED	
• Channel status display	Yes; Green LED
• for module diagnostics	Yes; Green/red LED
• For load voltage monitoring	Yes; Green LED
Potential separation	
between the load voltages	Yes
Potential separation channels	
• between the channels, in groups of	8
• between the channels and backplane bus	Yes
• between the channels and the power supply of the electronics	No; 8 channels are non-isolated and 8 channels are isolated from supply voltage 1L+
Isolation	
Isolation tested with	707 V DC (type test)
Degree and class of protection	
IP degree of protection	IP65/67
Ambient conditions	
Ambient temperature during operation	
• min.	-25 °C
• max.	55 °C
Connection method	
Design of electrical connection for the inputs and outputs	M12, 5-pole
Power supply	M8, 4-pole
ET-Connection	
• ET-Connection	M8, 4-pin, shielded
Dimensions	
Width	45 mm
Height	159 mm
Depth	40 mm
Weights	

Weight, approx.

195 g

last modified:

10/31/2018 