

SIMATIC DP, ET 200eco PN, IO-Link master, 4IO-L, 4xM12, Degree of protection IP67



General information	
Vendor identification (VendorID)	002AH
Device identifier (DeviceID)	0306H
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Load voltage 2L+	
Rated value (DC)	24 V
Reverse polarity protection	Yes; against destruction; load increasing
Input current	
Current consumption, typ.	100 mA
from supply voltage 1L+, max.	4 A
from load voltage 2L+, max.	4 A
Encoder supply	
Number of outputs	4
24 V encoder supply	

- Short-circuit protection Yes; per channel, electronic
- Output current, max. 500 mA; Per channel

Power loss

Power loss, typ. 4.8 W

IO-Link

Number of ports	4
• of which simultaneously controllable	4
IO-Link protocol 1.0	Yes
IO-Link protocol 1.1	Yes
Transmission rate	4.8 kBaud (COM1); 38.4 kBaud (COM2), 230 kBaud (COM3)
Size of process data, input per port	32 byte
Size of process data, input per module	128 bytes + 4 bytes PQI
Size of process data, output per port	32 byte
Size of process data, output per module	128 byte
Memory size for device parameter	2 kbyte; for each port
Master backup	Possible with function block IO_LINK_MASTER
Configuration without S7-PCT	Possible; autostart/manual function
Cable length unshielded, max.	20 m

Operating modes

- IO-Link Yes
- DI Yes
- DQ Yes; max. 100 mA

Connection of IO-Link devices

- Port type A Yes; via 3-core cable
- Port type B Yes; Additional device supply: max. 2 A per port, max. 4 A per module

Interfaces

Transmission procedure	100BASE-TX
Number of PROFINET interfaces	1

1. Interface

Interface types

- integrated switch Yes
- M12 port Yes

Interface types

M12 port

- Autonegotiation Yes
- Autocrossing Yes
- Transmission rate, max. 100 Mbit/s

Protocols

Supports protocol for PROFINET IO	Yes
-----------------------------------	-----

PROFINET CBA	No
PROFIsafe	No
PROFINET IO Device	
Services	
— IRT with the option "high flexibility"	Yes
Open IE communication	
• TCP/IP	No
• SNMP	Yes
• DCP	Yes
• LLDP	Yes
• ping	Yes
• ARP	Yes
Interrupts/diagnostics/status information	
Diagnostics function	Yes
Alarms	
• Diagnostic alarm	Yes
Diagnostic messages	
• Diagnostic information readable	Yes
• Monitoring the supply voltage	Yes; Green "ON" LED
• Short-circuit	Yes; Device supply to M
• Group error	Yes; Red/yellow "SF/MT" LED
Potential separation	
between the load voltages	Yes
between load voltage and all other switching components	No
between Ethernet and electronics	Yes
Isolation	
tested with	
• 24 V DC circuits	707 V DC (type test)
• Interface	1 500 V; According to IEEE 802.3
Degree and class of protection	
IP degree of protection	IP65/67
Standards, approvals, certificates	
Suitable for safety-related tripping of standard modules	No
Connection method	
Design of electrical connection	3/5-pin M12 round connectors
Dimensions	
Width	30 mm
Height	200 mm

Depth	49 mm
Weights	
Weight, approx.	550 g
last modified:	10/31/2018