

Power Contactors for Switching Motors

Accessories and Spare Parts for SIRIUS 3RT Contactors and SIRIUS 3RH2 Contactor Relays

Accessories

Terminal modules/adapters

Selection and ordering data

For con- tactors	Size	Version	SD	Screw terminals	PU (UNIT, SET, M)	PS*	PG
Type			d	Article No.	Price per PU		
Links for paralleling for main circuits							
The links for paralleling (insulated) can be reduced by one pole. With connecting terminal							
3-pole							
	3RT201	S00	• Max. conductor cross-section: 25 mm ² , stranded	▶ 3RT1916-4BB31	1	1 unit	41B
3RT1916-4BB31							
	3RT202	S0	• Max. conductor cross-section: 50 mm ² , stranded	2 3RT2926-4BB31	1	1 unit	41B
3RT2926-4BB31							
	3RT203	S2	• Max. conductor cross-section: 120 mm ² , stranded	▶ 3RT1936-4BB31	1	1 unit	41B
3RT1936-4BB31							
	3RT204, 3RT244	S3	• Max. conductor cross-section: 185 mm ² , stranded A cover plate is included for touch protection (can only be used when box terminal is removed).	2 3RT1946-4BB31	1	1 unit	41B
3RT1946-4BB31							
4-pole							
	3RT231, 3RT251	S00	• Max. conductor cross-section: 25 mm ² , stranded	15 3RT1916-4BB41	1	1 unit	41B
3RT1916-4BB41							