

Motor Starter Protectors/Circuit Breakers

SIRIUS 3RV2 Motor Starter Protectors/Circuit Breakers

Accessories

Mounting accessories


Link modules

Actuating voltage of contactor	Size 3RT2 contactors	3RV2 motor starter protectors/ circuit breakers	SD	Article No.	Price per PU	PU (UNIT, SET, M)	PS*	PG
			d					

Link modules for motor starter protector to contactor¹⁾



3RA2921-1AA00



3RA2931-1AA00



3RA2911-2AA00



3RA2911-1CA00

For mechanical and electrical connection between motor starter protector and contactor with screw terminals

Single-unit packaging

AC/DC	S00	S00/S0	►
AC	S0	S00/S0	2
DC	S0	S00/S0	2
AC/DC	S2	S2	►
AC/DC	S3	S3	►

Multi-unit packaging

AC/DC	S00	S00/S0	►
AC	S0	S00/S0	2
DC	S0	S00/S0	2
AC/DC	S2	S2	►
AC/DC	S3	S3	►

Screw terminals



3RA1921-1DA00	1	1 unit	41B
3RA2921-1AA00	1	1 unit	41B
3RA2921-1BA00	1	1 unit	41B
3RA2931-1AA00	1	1 unit	41B
3RA1941-1AA00	1	1 unit	41B
3RA1921-1D	1	10 units	41B
3RA2921-1A	1	10 units	41B
3RA2921-1B	1	10 units	41B
3RA2931-1A	1	5 units	41B
3RA1941-1A	1	5 units	41B

For mechanical and electrical connection between motor starter protector and contactor with spring-type terminals

Single-unit packaging

AC/DC	S00	S00	►
AC ²⁾	S0	S0	►
DC	S0	S0	►

Multi-unit packaging

AC/DC	S00	S00	►
AC ²⁾	S0	S0	►
DC	S0	S0	►

Spring-type terminals



3RA2911-2AA00	1	1 unit	41B
3RA2921-2AA00	1	1 unit	41B
3RA2921-2AA00	1	1 unit	41B
3RA2911-2A	1	10 units	41B
3RA2921-2A	1	10 units	41B
3RA2921-2A	1	10 units	41B

Spacers²⁾

For compensating the height on AC contactors

Single-unit packaging	S0	S0	2
Multi-unit packaging	S0	S0	2

3RA2911-1CA00	1	1 unit	41B
3RA2911-1C	1	5 units	41B

¹⁾ The link modules for motor starter protector to contactor cannot be used for 3RV2.21-4PA1., 3RV2.21-4FA1., 3RV2.31-4K.1., 3RV2.31-4R.1., 3RV2.32-4K.1., 3RV2.32-4R.1., 3RV27, 3RV28 and 3RV1011 motor starter protectors/circuit breakers.

²⁾ A spacer for height compensation on AC contactors size S0 is optionally available.

Note:

Link modules can be used in


- Size S00: up to max. 16 A
- Size S0: up to max. 32 A
- Size S2: up to max. 65 A

Motor Starter Protectors/Circuit Breakers

SIRIUS 3RV2 Motor Starter Protectors/Circuit Breakers

Accessories

Mounting accessories

Actuating voltage of contactor	Size	3RV2 motor starter protectors/circuit breakers	SD	Article No.	Price per PU	PU (UNIT, SET, M)	PS*	PG
	3RT2 contactors		d					
Hybrid link modules for motor starter protector to contactor¹⁾								
	Mechanical and electrical connection between motor starter protector with screw terminals and contactor with spring-type terminals							
	Single-unit packaging							
	AC/DC	S00	S00	▶	3RA2911-2FA00	1	1 unit	41B
	AC ²⁾ /DC	S0	S0	▶	3RA2921-2FA00	1	1 unit	41B
	Multi-unit packaging							
	AC/DC	S00	S00	▶	3RA2911-2F	1	10 units	41B
	AC ²⁾ /DC	S0	S0	2	3RA2921-2F	1	10 units	41B
	Spacers²⁾							
	For compensating the height on AC contactors							
	Single-unit packaging	S0	S0	2	3RA2911-1CA00	1	1 unit	41B
	Multi-unit packaging	S0	S0	2	3RA2911-1C	1	5 units	41B

¹⁾ The hybrid link modules for motor starter protector to contactor cannot be used for 3RV2.21-4PA1., 3RV2.21-4FA1., 3RV27, 3RV28 and 3RV1011 motor starter protectors/circuit breakers. They are suitable only for constructing direct-on-line starters.

²⁾ A spacer for height compensation on AC contactors size S0 is optionally available.

Note:

Hybrid link modules in size S00 can be used up to max. 16 A and in size S0 up to max. 32 A.

For motor starter protectors/circuit breakers	Version	SD	Screw terminals	PU (UNIT, SET, M)	PS*	PG
Type		d	Article No.	Price per PU		
Motor feeder connectors for motor starter protectors/circuit breakers with screw terminals						
	Adapters for motor starter protectors/circuit breakers					
	Ambient temperature $T_{u \max.} = 60^\circ\text{C}$					
3RV2.2	Size S0, rated operational current I_e at 400 V 3 AC: 25 A	5	3RT1926-4RD01		1	1 unit 41B
	Motor feeder connectors for motor starter protectors/circuit breakers					
	Size S0					
3RV2.2		5	3RT1900-4RE01		1	1 unit 41B

Load Feeders and Motor Starters for Use in the Control Cabinet

SIRIUS 3RA2 Load Feeders

Accessories

For motor starter protectors	For contactors	Version	SD	Article No.	Price per PU	PU (UNIT, SET, M)	PS*	PG
Size	Size		d					
RS assembly kits for reversing duty and 60-mm busbar systems								
RS assembly kits for screw terminals				Screw terminals 				
S00, S0	S00	Comprising:	2	3RA2913-1DB1		1	1 unit	41B
S0	S0	• Wiring kit for main and auxiliary circuit	2	3RA2923-1DB1		1	1 unit	41B
S00	S0	• Busbar adapters	2	3RA2923-1EB1		1	1 unit	41B
		• Device holders						
		• Two connecting wedges						
		• Mechanical interlocks						
		• Two connecting clips for two contactors						
		• Fixing accessories						
		Link modules must be ordered separately.						
S2	S2	Comprising:	2	3RA2933-1DB1		1	1 unit	41B
		• Wiring kit for main and auxiliary circuit						
		• Busbar adapters						
		• Mechanical interlocks						
		• Two connectors for two contactors						
		• Fixing accessories						
		Link modules must be ordered separately.						
RS assembly kits for spring-type terminals				Spring-type terminals 				
S00	S00	Comprising:	2	3RA2913-1DB2		1	1 unit	41B
S0	S0	• Wiring kit for main and auxiliary circuit	2	3RA2923-1DB2		1	1 unit	41B
		• Busbar adapters						
		• Device holders						
		• Two connecting wedges						
		• Mechanical interlocks						
		• Two connectors for two contactors						
		• Two spacers (for size S0 only)						
		• Fixing accessories						
		Link modules must be ordered separately.						

For graphic overviews for RS assembly kits, [see page 8/15 onwards](#).

For motor starter protectors	For contactors	Version	SD	Article No.	Price per PU	PU (UNIT, SET, M)	PS*	PG
Size	Size		d					
Connecting wedges								
		For mechanical linking of busbar adapters and device holders or of standard mounting rail adapters (2 units per combination required)	2	8US1998-1AA00		100	100 units	140
Spacers								
		For height compensation on AC contactors size S0 with spring-type terminals		Spring-type terminals 				
	S0	Single-unit packaging	2	3RA2911-1CA00		1	1 unit	41B
	S0	Multi-unit packaging	2	3RA2911-1C		1	5 units	41B