



Figure similar

MLFB-Ordering data

6SL3211-1PB21-0UL0

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.85
Number of phases	1 AC	Offset factor $\cos \varphi$	0.95
Line voltage	200 ... 240 V ± 10 %	Efficiency η	0.96
Line frequency	47 ... 63 Hz	Sound pressure level (1m)	62 dB
Rated current (LO)	24.00 A / 13.90 A	Power loss	0.12 kW
Rated current (HO)	20.90 A / 12.10 A	Filter class (integrated)	-
Output		Ambient conditions	
Number of phases	3 AC	Cooling	Internal air cooling
Rated voltage	230 V	Cooling air requirement	0.009 m ³ /s (0.325 ft ³ /s)
Rated current (LO)	10.40 A	Installation altitude	1000 m (3280.84 ft)
Rated current (HO)	7.40 A	Ambient temperature	
Max. output current	15.60 A	Operation LO	-5 ... 40 °C (23 ... 104 °F)
Rated power IEC 230V (LO)	2.20 kW	Operation HO	-5 ... 50 °C (23 ... 122 °F)
Rated power NEC 240V (LO)	3.00 hp	Transport	-25 ... 55 °C (-13 ... 131 °F)
Rated power IEC 230V (HO)	1.50 kW	Storage	-25 ... 55 °C (-13 ... 131 °F)
Rated power NEC 240V (HO)	2.00 hp	Relative humidity	
Pulse frequency	4 kHz	Max. operation	95 % RH, condensation not permitted
Output frequency for vector control	0 ... 200 Hz		
Output frequency for V/f control	0 ... 550 Hz		

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

SIEMENS

Data sheet for SINAMICS Power Module PM240-2


MLFB-Ordering data

6SL3211-1PB21-0UL0



Mechanical data	Connections
Degree of protection	IP20 / UL open type
Size	FSB
Net weight	3.40 kg (7.50 lb)
Width	154 mm (6.06 in)
Height	345 mm (13.58 in)
Depth	171 mm (6.73 in)
Line side	
Version	Plug-in screw terminals
Conductor cross-section	1.50 ... 6.00 mm² (AWG 16 ... AWG 10)
Motor end	
Version	Plug-in screw terminals
Conductor cross-section	1.50 ... 6.00 mm² (AWG 16 ... AWG 10)

Converter losses to EN 50598-2*	
Efficiency class	?PMD_ACF685_001_000?
Comparison with the reference converter (90% / 100%)	-47.39 %



The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components.

*converted values

Max. motor cable length	
Shielded	50 m (164.04 ft)
Unshielded	100 m (328.08 ft)

Standards	
Compliance with standards	UL, cUL, CE, C-Tick (RCM), SEMI F47
CE marking	Low-voltage directive 2006/95/EC