

MLFB-Ordering data

6SL3211-1PE27-5UL0



Figure similar

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Rated data		General tech. specifications	
Input		Power factor λ	0.95
Number of phases	3 AC	Offset factor $\cos \varphi$	0.99
Line voltage	380 ... 480 V ± 10 %	Efficiency η	0.97
Line frequency	47 ... 63 Hz	Sound pressure level (1m)	63 dB
Rated current (LO)	70.00 A	Power loss	1.10 kW
Rated current (HO)	62.00 A	Filter class (integrated)	-
Output		Ambient conditions	
Number of phases	3 AC	Cooling	Internal air cooling
Rated voltage	400 V	Cooling air requirement	0.055 m ³ /s (1.942 ft ³ /s)
Rated current (LO)	75.00 A	Installation altitude	1000 m (3280.84 ft)
Rated current (HO)	60.00 A	Ambient temperature	
Max. output current	120.00 A	Operation LO	-20 ... 40 °C (-4 ... 104 °F)
Rated power IEC 400V (LO)	37.00 kW	Operation HO	-20 ... 50 °C (-4 ... 122 °F)
Rated power NEC 480V (LO)	50.00 hp	Transport	-40 ... 70 °C (-40 ... 158 °F)
Rated power IEC 400V (HO)	30.00 kW	Storage	-40 ... 70 °C (-40 ... 158 °F)
Rated power NEC 480V (HO)	40.00 hp	Relative humidity	
Pulse frequency	4 kHz	Max. operation	95 % RH, condensation not permitted
Output frequency for vector control	0 ... 200 Hz		
Output frequency for V/f control	0 ... 550 Hz		

Overload capability

Low Overload (LO)

1.1 x rated output current (i.e. 110 % overload) for 57 s with a cycle time of 300 s 1.5 x rated output current (i.e. 150 % overload) for 3 s with a cycle time of 300 s

High Overload (HO)

1.5 x output current rating (i.e., 150 % overload) for 57 s with a cycle time of 300 s 2 x output current rating (i.e., 200 % overload) for 3 s with a cycle time of 300 s

SIEMENS

Data sheet for SINAMICS Power Module PM240-2

MLFB-Ordering data

6SL3211-1PE27-5UL0



Figure similar

Mechanical data	Connections																								
<table><tr><td>Degree of protection</td><td>IP20 / UL open type</td></tr><tr><td>Size</td><td>FSD</td></tr><tr><td>Net weight</td><td>20.00 kg (44.09 lb)</td></tr><tr><td>Width</td><td>275 mm (10.83 in)</td></tr><tr><td>Height</td><td>517 mm (20.35 in)</td></tr><tr><td>Depth</td><td>237 mm (9.33 in)</td></tr></table>	Degree of protection	IP20 / UL open type	Size	FSD	Net weight	20.00 kg (44.09 lb)	Width	275 mm (10.83 in)	Height	517 mm (20.35 in)	Depth	237 mm (9.33 in)	<table><tr><td colspan="2">Line side</td></tr><tr><td>Version</td><td>screw-type terminal</td></tr><tr><td>Conductor cross-section</td><td>10.00 ... 35.00 mm² (AWG 8 ... AWG 2)</td></tr><tr><td colspan="2">Motor end</td></tr><tr><td>Version</td><td>Screw-type terminals</td></tr><tr><td>Conductor cross-section</td><td>10.00 ... 35.00 mm² (AWG 8 ... AWG 2)</td></tr></table>	Line side		Version	screw-type terminal	Conductor cross-section	10.00 ... 35.00 mm² (AWG 8 ... AWG 2)	Motor end		Version	Screw-type terminals	Conductor cross-section	10.00 ... 35.00 mm² (AWG 8 ... AWG 2)
Degree of protection	IP20 / UL open type																								
Size	FSD																								
Net weight	20.00 kg (44.09 lb)																								
Width	275 mm (10.83 in)																								
Height	517 mm (20.35 in)																								
Depth	237 mm (9.33 in)																								
Line side																									
Version	screw-type terminal																								
Conductor cross-section	10.00 ... 35.00 mm² (AWG 8 ... AWG 2)																								
Motor end																									
Version	Screw-type terminals																								
Conductor cross-section	10.00 ... 35.00 mm² (AWG 8 ... AWG 2)																								
Converter losses to EN 50598-2*																									
<table><tr><td>Efficiency class</td><td>IE2</td></tr><tr><td>Comparison with the reference converter (90% / 100%)</td><td>-0.44 %</td></tr></table>	Efficiency class	IE2	Comparison with the reference converter (90% / 100%)	-0.44 %	<table><tr><td colspan="2">DC link (for braking resistor)</td></tr><tr><td>Version</td><td>Screw-type terminals</td></tr><tr><td>Conductor cross-section</td><td>2.50 ... 16.00 mm² (AWG 14 ... AWG 6)</td></tr><tr><td>Cable length</td><td>10 m (32.81 ft)</td></tr><tr><td>PE connection</td><td>Screw-type terminals</td></tr><tr><td colspan="2">Max. motor cable length</td></tr><tr><td>Shielded</td><td>200 m (656.17 ft)</td></tr><tr><td>Unshielded</td><td>300 m (984.25 ft)</td></tr></table>	DC link (for braking resistor)		Version	Screw-type terminals	Conductor cross-section	2.50 ... 16.00 mm² (AWG 14 ... AWG 6)	Cable length	10 m (32.81 ft)	PE connection	Screw-type terminals	Max. motor cable length		Shielded	200 m (656.17 ft)	Unshielded	300 m (984.25 ft)				
Efficiency class	IE2																								
Comparison with the reference converter (90% / 100%)	-0.44 %																								
DC link (for braking resistor)																									
Version	Screw-type terminals																								
Conductor cross-section	2.50 ... 16.00 mm² (AWG 14 ... AWG 6)																								
Cable length	10 m (32.81 ft)																								
PE connection	Screw-type terminals																								
Max. motor cable length																									
Shielded	200 m (656.17 ft)																								
Unshielded	300 m (984.25 ft)																								
	<table><tr><th colspan="2">Standards</th></tr><tr><td>Compliance with standards</td><td>UL, cUL, CE, C-Tick (RCM), SEMI F47</td></tr><tr><td>CE marking</td><td>Low-voltage directive 2006/95/EC</td></tr></table>	Standards		Compliance with standards	UL, cUL, CE, C-Tick (RCM), SEMI F47	CE marking	Low-voltage directive 2006/95/EC																		
Standards																									
Compliance with standards	UL, cUL, CE, C-Tick (RCM), SEMI F47																								
CE marking	Low-voltage directive 2006/95/EC																								

The percentage values show the losses in relation to the rated apparent power of the converter.

The diagram shows the losses for the points (as per standard EN 50598) of the relative torque generating current (I) over the relative motor stator frequency(f). The values are valid for the basic version of the converter without options/components.

*converted values