

SIGUARD SWITCHING ELEMENT, 2NC MOULDED PLASTIC
HOUSING 5XX88 CONN.CABLE 3M LIYY 4X0,25SQMM
(SWITCHING MAGNET REQUIRED: 3SE67042BA)



Figure similar

Product brand name	SIRIUS
Product designation	Magnetically operated switch
Design of the product	rectangular sensor unit
Product type designation	3SE66
Suitability for use safety-related circuits	Yes

General technical data	
Product function	
• positive opening	No
• cross-circuit/short-circuit recognition	No
Type of voltage of the operating voltage	AC/DC
Protection class IP	IP67
Shock resistance	
• acc. to IEC 60068-2-27	Sinusoidal half-wave 30g / 11 ms
Vibration resistance	
• acc. to IEC 60068-2-6	10 ... 55 Hz: 1 mm
Equipment marking	

• acc. to DIN 40719 extended according to IEC 204-2 acc. to IEC 750	S
• acc. to DIN EN 61346-2	S
• acc. to DIN EN 81346-2	S
Type of voltage	AC/DC
Height of the sensor	13 mm
Length of the sensor	88 mm
Width of the sensor	25 mm
Material of the active sensor area	plastic
Operating voltage rated value	100 V
Operating current rated value	250 mA
Operating power rated value	3 W
Number of NC contacts	
• for auxiliary contacts	2
Number of NO contacts	
• for auxiliary contacts	0
Number of CO contacts for auxiliary contacts	0

Enclosure

Design of the housing	block
Material of the enclosure	plastic
Material of cable sheath	PVC

Actuator

Design of the operating mechanism	magnet
--	--------

Contact

Circuit principle	reed switches
Switching frequency	5 Hz
Safe operating distance OFF	15 mm
Safe operating distance ON	5 mm
Design of the switching function	NC contact

Connections/Terminals

Type of electrical connection	cable, 3 m
Wire length	3 m

Safety related data

Safety Integrity Level (SIL) acc. to IEC 61508	3
Performance level (PL) acc. to EN ISO 13849-1	e
Category acc. to EN 954-1	4

Ambient conditions

Ambient temperature	
• during operation	-25 ... +70 °C
• during storage and transport	-25 ... +70 °C

Inputs/ Outputs

Type of switching output Reed contacts

Display

Evaluation version required yes

Installation/ mounting/ dimensions

Mounting type screw fixing

Certificates/approvals

General Product Approval	Functional Safety/Safety of Machinery	Declaration of Conformity	other
--------------------------	---------------------------------------	---------------------------	-------



[Type Examination Certificate](#)

[Miscellaneous](#)



[Confirmation](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SE6604-2BA>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SE6604-2BA>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3SE6604-2BA>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SE6604-2BA&lang=en

last modified:

07/03/2017