




Grounding Blocks




Ordering and Technical Information ①	4mm ²			6mm ²			10mm ²		
									
	Single circuit grounding terminal block			Single circuit grounding terminal block			Single circuit grounding terminal block		
	Catalog Number	Price Ea. (Std Pkg)	Pkg. Qty	Catalog Number	Price Ea. (Std Pkg)	Pkg. Qty	Catalog Number	Price Ea. (Std Pkg)	Pkg. Qty
Terminal - green/yellow	V7-WG4	9.00	50	V7-WG6	9.50	50	V7-WG10S	11.50	10
Accessories (also see pages N26 to N31)									
End Barrier	V7-EB3-Y	1.95	50	V7-EB10-Y	1.50	50	V7-EB10-Y	1.50	50
End Anchors									
DIN Rail — Normal Duty	V7-EA35	1.75	50	V7-EA35	1.75	50	V7-EA35	1.75	50
DIN Rail — Heavy Duty	V7-EAH35	7.00	10	V7-EAH35	7.00	10	V7-EAH35	7.00	10
DIN Rail — Snap-in	V7-ER35	1.80	50	V7-ER35	1.80	50	V7-ER35	1.80	50
Other Accessories									
Group Marking Carrier	V7-GM35	3.60	10	V7-GM35	3.60	10	V7-GM35	3.60	10
Marking Systems ②									
Blank Tags (cards of 100)	V7-SM6X12	12.00	5	V7-SM6X12	12.00	5	V7-SM8X12	12.00	5
Pre-printed Tags (sticks of 10)	V7-MP ③	2.70	10	V7-MP ③	2.70	10			
Terminal Block Specifications									
Approvals			IEC			IEC			IEC
Voltage Rating	~	~	~	~	~	~	~	~	~
Maximum Current	Grounding			Grounding			Grounding		
Wire Range (Rated Cross Section)	#22... #14 AWG	#22... #12 AWG	4 mm ²	#22... #10 AWG	#22... #10 AWG	6 mm ²	#22... #8 AWG	#22... #8 AWG	10 mm ²
Wire Strip Length	0.43" (11 mm)			0.47" (12 mm)			0.43" (11 mm)		
Recommended Tightening Torque	5.6...6.8 lb-in. (0.7 Nm)			5.6...6.8 lb-in. (0.7 Nm)			7.1 lb-in. (0.8 Nm)		
Density	50 pcs./ft (166/m)			43 pcs./ft (142/m)			38 pcs./ft (125/m)		
Insulation Temperature Range	-40°...+195°F (-40°...+90°C)			-40°...+195°F (-40°...+90°C)			-40°...+195°F (-40°...+90°C)		
Mounting Rail	Fits all types shown on page N32			Fits all types shown on page N32			Fits all types shown on page N32		

① Refer to pages N24...N29 for a listing of all V7-W accessories.

② Custom marking tags available. See page N45 for full offering.

③ Catalog number is not complete. See pages N42...N43.

Accessories

Ordering Instructions:						pg. N5	pg. N5	pg. N5	pg. N6	pg. N6
1. Identify accessory required.						-W3 Through	-W4 Through	-W6 Through	-W10 Through	-W16S Through
2. Identify terminal block along top of table.										
3. Use matrix to determine which Accessory Type to order.										
Component	Description	Type	Catalog Number	Price Each	Std. Pkg.					
	End Barrier Provides insulation for the last terminal block in a group. Gray unless noted.		V7-EB10	1.20	50					
		(shown)	V7-EB3	1.20	50	■	■			
			V7-EB3TW	1.35	50					
		(shown)	V7-EB35	2.25	25					
			V7-EBD3	1.95	50					
		yellow	V7-EBD3-Y	1.95	50					
			V7-EBD6	2.25	50					
			V7-EBD4P	2.00	50					
			V7-EBKD3	1.20	50					
			V7-EBR3	1.35	50					
			V7-EBTF3	1.95	50					
			V7-EBTS3	1.95	50					
		(shown)	V7-N37	1.50	50					
		yellow	V7-EB10-Y	1.50	50					
yellow	V7-EB3-Y	1.20	50							
	V7-EBFB10V	1.45	50							
	End Anchor (Screw type) Anchors a row of blocks or a single block	Standard (shown)	V7-EA35	1.75	50	■	■	■	■	■
		Heavy Duty	V7-EAH35	7.00	10	■	■	■	■	■
		Snap In (shown)	V7-ER35	1.80	50	■	■	■	■	■
	Side Jumpers Insulated, fit in wire openings of blocks		V7-SJ5-10	3.60	10	■				
			V7-SJ6-10	4.45	10		■			
			V7-SJ8-10	5.10	10				■	
		(shown)	V7-SJFB8-10	8.40	10					
		Blue	V7-SJT5-20-B	10.50	10					
		Red	V7-SJT5-20-R	10.50	10					
	Non-insulated	V7-N49	6.10	10						
	Insulating Side Jumper Sleeve For use with catalog # V7-N49		V7-SJS	2.70	10					
	Replacement Fuse Knob		V7-FCM	5.25	50					
	Center Jumpers Uninsulated, screw into threaded hole in center of block (See page N28 for more Center Jumpers)	2 pole	V7-CJ5-2	2.25	10	■				
		3 pole	V7-CJ5-3	3.30	10	■				
		10 pole	V7-CJ5-10	8.90	10	■				
		50 pole	V7-CJ5-50	42.00	5	■				
		2 pole	V7-CJ6-2	2.40	10		■			
		3 pole	V7-CJ6-3	3.50	10		■			
		10 pole	V7-CJ6-10	9.40	10		■			
50 pole	V7-CJ6-50	37.00	5		■					

Note: For full line of marking accessories see the Marking Section beginning on page N38.

End Barriers

End Barriers

A 3D perspective view of a white, rectangular end barrier with a recessed rectangular opening in the center. Dimension lines indicate: 'B' for the height, 'A' for the width, and 'C' for the depth.

Catalog #	A	B	C
V7-EB3	1.46"	1.38"	0.06"
V7-EB3-Y	(37 mm)	(35 mm)	(1.5mm)
V7-EB10	1.77"	1.61"	0.06"
V7-EB10-Y	(45 mm)	(41 mm)	(1.5 mm)

A 3D perspective view of a white, rectangular end barrier with a recessed rectangular opening and two small circular features at the bottom. Dimension lines indicate: '2.80" (71 mm)' for the height and '2.36" (60 mm)' for the width. A small 'C' dimension line indicates a depth of '0.08" (2 mm)'.

V7-EB35

A 3D perspective view of a white, rectangular end barrier with a recessed rectangular opening and a small circular feature at the bottom. Dimension lines indicate: '1.91" (48.6 mm)' for the height and '2.44" (62 mm)' for the width. A small 'C' dimension line indicates a depth of '0.06" (1.5 mm)'.

V7-EBD3/Y

A 3D perspective view of a white, rectangular end barrier with a recessed rectangular opening and a small circular feature at the bottom. Dimension lines indicate: '1.64" (41.6 mm)' for the height and '1.79" (45.4 mm)' for the width. A small 'C' dimension line indicates a depth of '0.06" (1.5 mm)'.

V7-EB3TW

A 3D perspective view of a white, rectangular end barrier with a recessed rectangular opening and a small circular feature at the bottom. Dimension lines indicate: '1.74" (44.1 mm)' for the height and '2.61" (66.2 mm)' for the width. A small 'C' dimension line indicates a depth of '0.06" (1.5 mm)'.

V7-EBTS3

A 3D perspective view of a white, rectangular end barrier with a recessed rectangular opening and a small circular feature at the bottom. Dimension lines indicate: '1.74" (44.1 mm)' for the height and '3.51" (89.1 mm)' for the width. A small 'C' dimension line indicates a depth of '0.06" (1.5 mm)'.

V7-EBTF3

A 3D perspective view of a white, rectangular end barrier with a recessed rectangular opening and a small circular feature at the bottom. Dimension lines indicate: '1.35" (34.3 mm)' for the height and '1.81" (46 mm)' for the width. A small 'C' dimension line indicates a depth of '0.06" (1.5 mm)'.

V7-EBKD3

A 3D perspective view of a white, rectangular end barrier with a recessed rectangular opening and a small circular feature at the bottom. Dimension lines indicate: '2.36" (60 mm)' for the height and '2.97" (75.4 mm)' for the width. A small 'C' dimension line indicates a depth of '0.06" (1.5 mm)'.

V7-EBD4P

A 3D perspective view of a white, rectangular end barrier with a recessed rectangular opening and a small circular feature at the bottom. Dimension lines indicate: '2.52" (64 mm)' for the height and '2.91" (74 mm)' for the width. A small 'C' dimension line indicates a depth of '0.08" (2 mm)'.

V7-EBD6

A 3D perspective view of a white, rectangular end barrier with a recessed rectangular opening and a small circular feature at the bottom. Dimension lines indicate: '2.19" (55.5 mm)' for the height and '1.65" (42 mm)' for the width. A small 'C' dimension line indicates a depth of '0.06" (1.5 mm)'.

V7-EBR3

A 3D perspective view of a white, rectangular end barrier with a recessed rectangular opening and a small circular feature at the bottom. Dimension lines indicate: '1.96" (49.8 mm)' for the height and '2.81" (71.4 mm)' for the width. A small 'C' dimension line indicates a depth of '0.11" (2.8 mm)'.

V7-N37