



Figure similar

Data sheet for SIMOTICS M-1PH8

Article No. : 1PH8286-1HF23-2AD2

Client order no. :
Order no. :
Offer no. :
Remarks :

Item no. :
Consignment no. :
Project :

Engineering data

		P _N [kW]	M _N [Nm]	I _N [A]	U _N [V]	f _N [Hz]	n _N [rpm]	M _{max} [Nm]	I _{max} [A]	n _{max} [rpm]	M ₀ [Nm]	I ₀ [A]	η	cos φ	I _μ [A]
Δ	ALM 400V	328.0	1,790.0	540.0	400	58.7	1,750	4,475	1,350.0	3,300	1,790.0	540	0.967	0.900	182.0
	BLM/SLM 400V	281.0	1,789.0	540.0	343	50.4	1,500	4,473	1,350.0	3,300	1,789.0	540	0.966	0.900	181.0
	ALM/BLM/SLM 480V	375.0	1,791.0	550.0	455	67.0	2,000	4,477	1,375.0	3,300	1,791.0	550	0.968	0.900	180.0

Mechanical data

Motor type	Squirrel cage asynchronous motor
Shaft height	280
Cooling	Water cooling
Vibration severity grade	A
Shaft and flange accuracy	N
Degree of protection	IP55
Design acc. to Code I	IM B35 with A660 flange (IM V35)
Temperature monitoring	Pt1000 temperature sensor in the stator winding
Color	Standard (Anthracite RAL 7016)
Type of the bearing	Standard
Shaft end	Feather key with half key balancing
Encoder system	Incremental encoder HTL 1024 S/R, max. encoder speed = 9000 rpm

Physical constants

Thermal time constant	33 min
Moment of inertia	52,000 kgcm ²
Weight (approx.)	1,490 kg

Connection

Type of electrical connection	Terminal box
Position of the connection	NDE top
Power connection	DE
Signal connection	right
Terminal box designation	1XB7712-P03

Cooling data and sound pressure level

Flow rate, min.	35 l/min
Sound pressure level L _{pA} (1m) motor rated load, tolerance + 3dB	72 dB ¹⁾
Pressure drop	0.6 bar
NDE thread connection	0.5 Inches

Cooling water specification

pH value	6 ... 9
Total hardness	1.7 mmol/l
Electrical conductivity	2,000 μS/cm
Chloride ions	250 mg/l
Sulfate ions	240 mg/l
Nitrate ions	50 mg/l
Dissolved substances	340 mg/l
Maximum particle size	100 μm
Antifreeze/corrosion protection	20 ... 30 %

¹⁾ at a rated frequency of 2 kHz and a speed range of up to 3300 rpm