

Semiconductor relay, 1-phase 3RF2 Overall width 45 mm, 70 A 48-460 V / 24 V DC screw terminal



Product brand name	SIRIUS
Product designation	solid-state relay
Product type designation	3RF20
General technical data	
Product function	zero-point switching
Power loss [W] / for rated value of the current / at AC / in hot operating state	94 W
Insulation voltage • rated value	600 V
Protection class IP	IP20
Shock resistance / acc. to IEC 60068-2-27	15g / 11 ms
Vibration resistance / acc. to IEC 60068-2-6	2g
Reference code / acc. to DIN 40719 extended according to IEC 204-2 / acc. to IEC 750	K
Reference code / acc. to DIN EN 81346-2	Q
Reference code / acc. to DIN EN 61346-2	Q
Main circuit	
Number of poles / for main current circuit	1
Number of NO contacts / for main contacts	1

Number of NC contacts / for main contacts	0
Operating voltage / at AC	
• at 50 Hz / rated value	48 ... 460 V
• at 60 Hz / rated value	48 ... 460 V
Operating frequency / rated value	50 ... 60 Hz
Relative symmetrical tolerance / of the operating frequency	10 %
Operating range relative to the operating voltage / at AC	
• at 50 Hz	40 ... 506 V
• at 60 Hz	40 ... 506 V
Operating current / minimum	500 mA
Operating current	
• at AC-1 / at 400 V / rated value	70 A
• at AC-51 / rated value	50 A
Rate of voltage rise / at the thyristor / for main contacts / maximum permissible	1 000 V/μs
Blocking voltage / at the thyristor / for main contacts / maximum permissible	1 200 V
Reverse current / of the thyristor	10 mA
Derating temperature	40 °C
Surge current resistance / rated value	1 200 A
I²t value / maximum	7 200 A ² ·s

Control circuit/ Control

Type of voltage / of the control supply voltage	DC
Control supply voltage / 1	
• at DC / rated value	30 V
• at DC	15 ... 24 V
Control supply voltage	
• at DC / initial value for signal <1> detection	15 V
• at DC / Full-scale value for signal<0> recognition	5 V
Control current / at minimum control supply voltage	
• at DC	2 mA
Control current / at DC / rated value	15 mA
Switch-on delay time	1 ms; additionally max. one half-wave
Off-delay time	1 ms; additionally max. one half-wave
Number of NC contacts / for auxiliary contacts	0
Number of NO contacts / for auxiliary contacts	0
Number of CO contacts / for auxiliary contacts	0

Installation/ mounting/ dimensions

Mounting type	screw fixing
• Side-by-side mounting	Yes

Height	58 mm
Width	45 mm
Depth	48 mm
Installation altitude / at height above sea level / maximum	1 000 m

Connections/ Terminals

Type of connectable conductor cross-sections • for main contacts — solid — finely stranded / with core end processing • at AWG conductors / for main contacts	2x (1.5 ... 2.5 mm ²), 2x (2.5 ... 6 mm ²) 2x (1 ... 2.5 mm ²), 2x (2.5 ... 6 mm ²), 1x 10 mm ² 2x (14 ... 10)
Type of connectable conductor cross-sections • for auxiliary and control contacts — solid — finely stranded / with core end processing — finely stranded / without core end processing • at AWG conductors / for auxiliary and control contacts	1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²) 1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²) 1x (0.5 ... 2.5 mm ²), 2x (0.5 ... 1.0 mm ²) 1x (AWG 20 ... 12)
Tightening torque / for main contacts / with screw-type terminals	2 ... 2.5 N·m
Tightening torque / for auxiliary and control contacts / with screw-type terminals	0.5 ... 0.6 N·m
Tightening torque [lbf·in] • for main contacts / with screw-type terminals • for auxiliary and control contacts / with screw-type terminals	7 ... 10.3 lbf·in 4.5 ... 5.3 lbf·in
Design of the thread / of the connection screw • for main contacts • of the auxiliary and control contacts	M4 M3
Wire stripping length / of the cable • for main contacts • for auxiliary and control contacts	10 mm 7 mm

Ambient conditions

Ambient temperature • during operation • during storage	-25 ... +60 °C -55 ... +80 °C
---	----------------------------------

Electromagnetic compatibility

Conducted interference • due to burst / acc. to IEC 61000-4-4 • due to conductor-earth surge / acc. to IEC 61000-4-5	2 kV / 5 kHz behavior criterion 2 2 kV behavior criterion 2
--	--

• due to conductor-conductor surge / acc. to IEC 61000-4-5 • due to high-frequency radiation / acc. to IEC 61000-4-6	1 kV behavior criterion 2
Electrostatic discharge / acc. to IEC 61000-4-2	140 dBuV in the frequency range 0.15 ... 80 MHz, behavior criterion 1
Conducted HF-interference emissions / acc. to CISPR11	4 kV contact discharging / 8 kV air discharging, behavior criterion 2
Field-bound HF-interference emission / acc. to CISPR11	Class A for industrial environment
	Class B for the domestic, business and commercial environments

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RF2070-1AA04>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RF2070-1AA04>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RF2070-1AA04>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RF2070-1AA04&lang=en

Short-circuit protection, design of the fuse link

https://www.automation.siemens.com/cd-static/material/info/3RF20_eng.pdf

Short-circuit protection, design of the fuse link

https://www.automation.siemens.com/cd-static/material/info/3RF21_eng.pdf

Short-circuit protection, design of the fuse link

https://www.automation.siemens.com/cd-static/material/info/3RF22_eng.pdf

Short-circuit protection, design of the fuse link

https://www.automation.siemens.com/cd-static/material/info/3RF23_eng.pdf

Short-circuit protection, design of the fuse link

https://www.automation.siemens.com/cd-static/material/info/3RF24_eng.pdf





