

button, 2 NC 20 A 1 key red, Lamp 230 V



Figure similar

Model	
Product brand name	SETRON
Product designation	Pushbutton
Design of the product	2 NC contacts
Type of light source	LED
Mounting type / for light source	others
Supply voltage	
Type of voltage	AC
Operating voltage / rated value	400 V
Protection class	
Protection class IP	IP20
Dissipation	
Power loss [W]	
• for rated value of the current / at AC / in hot operating state / per pole	0.6 W
• maximum	0.6 W

Current	
Current / rated value	20 A

Appearance	
Color	
• of the button	red

Product details	
Product component / Signal lamp	Yes
Number of NC contacts	2
Number of NO contacts	0
Number of CO contacts	0
Connectable conductor cross-section / for flexible conductor / with core end processing	
• minimum	1 mm ²
• maximum	6 mm ²
Connectable conductor cross-section / for rigid conductor	
• minimum	1 mm ²
• maximum	6 mm ²

Mechanical Design	
Height	90 mm
Depth	70 mm
Installation depth	70 mm
Number of width units	1
Net weight	83 g

Certificates	
Reference code	
• acc. to DIN EN 61346-2	S
• acc. to DIN EN 81346-2	S

General Product Approval	Declaration of Conformity	Test Certificates	other		
--------------------------	---------------------------	-------------------	-------	--	--



[Miscellaneous](#)

[Environmental Confirmations](#)

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5TE4824>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/5TE4824>

