

touch pen caps V2A, replacement caps for touch pen system for capacitive and resistive touch screens more information, quantity and content: see technical specifications



Figure similar

General information	
Product type designation	Touch pen caps
Control elements	
Frame size/design	
• Standard	Yes; threaded special cap for universal touch system
Installation type/mounting	
Wall mounting/direct mounting	Yes; can be used for touch pen system ELO and V2A
Standards, approvals, certificates	
CE mark	No; No CE marking obligation
RoHS conformity	Yes; FDA§177.2600 compliant
FDA-compliant	Yes; FDA§177.2600 compliant
Ambient conditions	
Suited for indoor use	Yes
Suited for outdoor use	Yes; only suitable under certain conditions due to different environmental conditions; replacement cycle can be increased
Ambient temperature during operation	
• min.	-40 °C; at temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended
• max.	80 °C; at temperatures below 10 °C and above 30 °C, the use of suitable gloves is recommended
Ambient temperature during storage/transportation	
• min.	-40 °C
• max.	80 °C
Relative humidity	
• Operation, max.	95 %
Accessories	
belongs to product	can be used for touch pen system ELO and V2A
Mechanics/material	
Material	
• Plastic	Yes; special cap only for resistive and capacitive touch systems
• Stainless steel	Yes; food safe, suitable for F&B
Color	stainless steel, polished
Torques/forces	
• Tightening torque, max.	Hand-tight
Dimensions	
Height	8 mm
Diameter	8 mm
Weights	

Weight (without packaging)	0.8 g
Weight (with packaging)	1.7 g
Scope of supply	
Delivery quantity in pieces	5; Caps for touch pen
Other	
Merchandise	Yes; touch replacement cap V2A
Manufacturer name	QUERUM products UG
Manufacturer's address	Wirtsstr. 23, 85110 Kipfenberg-Böhming, Germany
contacting the manufacturer	email: querumproducts@web.de
Target devices	For common capacitive and resistive touch systems
Note:	food safe, suitable for F&B
Usable in the following products	
• Product 1 • Product 2	6AV6881-0AV21-0AA0 6AV6881-0AV22-0AA0
last modified:	6/11/2021 