

SIMATIC IFP2200 PRO, Flat Panel, 22" display (16:9), Multitouch, suitable for pedestal and extension components, extended version max. 30m, 1920 x 1080 pixel, for 24V DC, displayport/DVI Interface, IP65, fully enclosed, neutral design



General information

Product type designation	IFP2200 PRO
Short designation	Flat Panel 22" PRO multi-touch ext.

Display

Design of display	TFT widescreen display, LED backlighting
Screen diagonal	22 in
Screen diagonal [cm]	56 cm
Display width	476 mm
Display height	268 mm
On Screen Display (OSD) configuration	No; Adjustable by means of software
Number of colors	16 777 216; 24 bit
Viewing angle	178° x 178°

Resolution (pixels)	
• Horizontal image resolution	1 920 Pixel
• Vertical image resolution	1 080 Pixel
• Pixel size, horizontal	0.2475 mm
• Pixel size, vertical	0.2475 mm

General features

• Brightness/contrast	250 cd/m ² / 1 000:1
• non-reflective and tempered mineral glass screen	Yes
• Detachable from computer unit	30 m
• Luminance	250 cd/m ²
Backlighting	
• Type of backlighting	LED
• MTBF backlighting (at 25 °C)	30 000 h; At 25°C
• Backlight dimmable	Yes; 0-100 %
Control elements	
Input device	
• Integrated mouse cursor control	Yes; Also externally via USB
Keyboard fonts	
• Function keys	No
— Number of function keys	0
Touch operation	
• Design as touch screen	Yes; Projective-capacitive
• Design as multi-touch screen	Yes; Projective-capacitive
• Monitor keyboard	Yes
Installation type/mounting	
Design	Support arm mounting
Support arm mounting	No
Stand mounting	Yes
Built-in unit	No; IP65 fully enclosed
maximum permitted forward tilt angle from vertical	45°
maximum permitted backward tilt angle from vertical	45°
Supply voltage	
Type of supply voltage	24 V DC
Rated value (DC)	24 V; PELV / SELV floating
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	2.5 A
Current consumption, max.	3 A
Inrush current, max.	2.8 A
Starting current inrush I ² t	0.5 A ² ·s
Power	
Active power input, typ.	40 W
Power loss	
Power loss, typ.	40 W

Power loss, max.	60 W
Interfaces	
Number of USB interfaces	2; USB 2.0 type A
USB on the rear	Yes; 2x onboard
Connection for keyboard/mouse	USB
Video interfaces	
• analog video signal (VGA)	No
• DVI-D	Yes
• DisplayPort	Yes; DisplayPort V1.1
Touch interfaces	
• USB	Yes
Degree and class of protection	
IP (all-round)	IP65
IP (at the front)	
• IP65 at front	Yes
IP (rear)	
• IP65 rear	Yes
NEMA (front)	
• Enclosure Type 4 at the front	Yes
• Enclosure Type 4x at the front	Yes
• NEMA4 at the front	Yes
• NEMA4X at the front	Yes
Standards, approvals, certificates	
CE mark	Yes
UL approval	Yes
cULus	Yes; Corresponds to UL 508
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes
Use in hazardous areas	
• ATEX Zone 2	Yes; Available soon
• ATEX Zone 22	Yes; Available soon
• IECEx Zone 2	Yes; Available soon
• IECEx Zone 22	Yes; Available soon
• cULus Class I Zone 2, Division 2	Yes; Available soon
• FM Class I Division 2	Yes; Available soon
Ambient conditions	
Ambient temperature during operation	
• min.	0 °C
• max.	45 °C
Ambient temperature during storage/transportation	

• min.	-20 °C
• max.	60 °C
Relative humidity	
• Operation, max.	95 %; no condensation
Vibrations	
• Vibration load in operation	10 m/s ²
• Vibration load during transport/storage	10 m/s ²
Shock testing	
• Shock load during operation	150 m/s ²
• Shock load during transport/storage	150 m/s ²
Mechanics/material	
Enclosure material (front)	With neutral design
• Aluminum	Yes
• Glass	Yes; at front
Dimensions	
Width	527 mm
Height	329 mm; Without basic adapter
Depth	94 mm; Without basic adapter
Width of the housing front	527 mm
Height of housing front	329 mm
Weights	
Weight without packaging	8.1 kg
Weight incl. packaging	11 kg
last modified:	01/29/2020 