

Data sheet

6GT2091-4FH20

Product type designation	Cable RS422, M12 / EN 175201-804
Product description	Highly flexible communication line (6-core) MOBY I/E/U plug-in cable, assembled, between ASM 456, RF160C, RF170C, RF18xC and SLG, PUR, trailing, length 2 m
Suitability for use	Plug-in cable for connecting a MOBY U SLG to a communication module
Wire length	2 m

Electrical data

Number of electrical connections	2
Type of electrical connection	M12 (male, 8 pin, straight) / EN 175201-804 (female, 7 pin, angled)
Loop resistance per length / maximum	160 mΩ/m
Insulation resistance coefficient	20 GΩ·m
Operating voltage	
• maximum	300 V

Mechanical data

Number of electrical cores	6
Design of the shield	Braided shield made of tin-plated copper wires
Outer diameter	
• of cable sheath	5.4 mm
Symmetrical tolerance of the outer diameter / of cable sheath	0.2 mm
Material	
• of the wire insulation	PVC
• of cable sheath	PUR
Color	
• of the insulation of data wires	DIN 47100
• of cable sheath	Black
Bending radius	
• with single bend / minimum permissible	21.6 mm
• with multiple bends / minimum permissible	43 mm
• with continuous bending	75 mm
Number of bending cycles	3000000
Tensile load / maximum	200 N
Weight per length	45 kg/km

Permitted ambient conditions

Ambient temperature	
• during operation	-30 ... +80 °C

• during storage • during transport • during installation	-30 ... +80 °C
	-30 ... +80 °C
	-30 ... +80 °C
Burning behavior	flame resistant according to IEC 60332-1-2
Chemical resistance	
• to mineral oil • to grease	resistant
	resistant
Radiological resistance / to UV radiation	resistant

Product properties, functions, components / general

Product feature	
• halogen-free • silicon-free	No
	Yes

Standards, specifications, approvals

UL/ETL listing / 300 V Rating	Yes
-------------------------------	-----

Further Information / Internet Links

Internet-Link	
• to website: Selector SIMATIC NET SELECTION TOOL • to website: Industrial communication • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAx Download Manager • to website: Industry Online Support	https://support.industry.siemens.com/cs/ww/en/view/67384964 http://www.siemens.com/ident/rfid https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com

last modified: 01/22/2019