

product description



Glass fiber-optic cable, sold by the meter, unassembled

FO FRNC Cable GP (50/ 125/OM4), halogen-free cable, splittable, for permanent routing, max. length 1000 m minimum order quantity 20 m sold by the meter

suitability for use

Halogen-free cable (acc. to IEC 61034-1 / 61034-2 and IEC 60754-1 / IEC 60754-2) for use indoors and outdoors with permanent installation, UL approval

version of the assembled FO cable

For assembly with four BFOC or SC connectors

cable designation

AT-W(ZN)HH 2G 50/125 OM4BI UV OM4

optical data

attenuation factor per length

- at 850 nm / maximum
- at 1300 nm / maximum

2.5 dB/km
0.7 dB/km

bandwidth length product

- at 850 nm
- at 1300 nm

3500 GHz·m
500 GHz·m

mechanical data

number of fibers / per FOC core

1

number of FO cores / per FOC cable

2

version of the FO conductor fiber

Multi-mode gradient fiber 50/125 µm, OM 4

design of the FOC core

Hollow core, filled, diameter 1400 µm

design of the fiber-optic cable

segmentable

outer diameter

- of the optical fibers
- of the optical fiber sheath
- of the FOC core sheath

50 µm
125 µm
2.9 mm

symmetrical deviation / of the outer diameter of the FOC core sheath

0.1 mm

outer diameter / of the cable

9.2 mm

symmetrical deviation / of the outer diameter of the line

0.3 mm

material

- of the fiber-optic cable core
- of the optical fiber sheath
- of the FOC core sheath
- of the fiber-optic cable sheath
- of the strain relief

Quartz glass
Quartz glass
FRNC
FRNC
Aramid fibers

color

- of the FOC core sheath
- of cable sheath

orange/black
green

bending radius

- with single bend / minimum permissible
- with multiple bends / minimum permissible

90 mm
135 mm

tensile load

during installation / short-term	1200 N
during operation / maximum	500 N
short-term shear force per length	500 N/cm
weight per length	85 kg/km
ambient conditions	
ambient temperature	
during operation	-40 ... +85 °C
during storage	-40 ... +85 °C
during transport	-40 ... +85 °C
during installation	-5 ... +50 °C
fire behavior	flame-resistant acc. to IEC 60332-1-2 and IEC 60332-3-22 (Cat. A)
class of burning behaviour / according to EN 13501-6	Eca
chemical resistance	
to mineral oil	acc. to IEC 60811-404 with test oil IRM 902 (acc. to ISO 1817), +70 °C, 4 h and +25 °C, 168 h
to grease	conditional resistance
to water	conditional resistance
radiological resistance / to UV radiation	resistant
product features, product functions, product components / general	
product feature	
halogen-free	Yes
silicon-free	Yes
product component / rodent protection	No
wire length	
for glass FOC / for 100BaseFX / for Industrial Ethernet / maximum	5000 m
for glass FOC / for 1000BaseSX / for Industrial Ethernet / maximum	1040 m
for glass FOC / for 1000BaseLX / for Industrial Ethernet / maximum	600 m
for glass FOC / with 10GBaseSR / for Industrial Ethernet / maximum	550 m
for glass FOC / for 10GBaseLX4 / for Industrial Ethernet / maximum	300 m
standards, specifications, approvals	
certificate of suitability	UL approval: cULus OFN (NEC Article 770, UL 1651) / CSA approval: OFN, FT4 (CSA Standard C22.2 No232)
RoHS conformity	Yes
reference code	
according to IEC 81346-2	WH
according to IEC 81346-2:2019	WHA
further information / internet-Links	
Internet-Link	
to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool
to website: Industrial communication	http://www.siemens.com/simatic-net
to website: Industry Mall	https://mall.industry.siemens.com
to website: Information and Download Center	http://www.siemens.com/industry/infocenter
to website: Selection guide for cables and connectors	https://sie.ag/2QdlxcP
to website: Image database	http://automation.siemens.com/bilddb
to website: CAx-Download-Manager	http://www.siemens.com/cax
to website: Industry Online Support	https://support.industry.siemens.com
last modified:	2/24/2022 