

BUILT-IN LUMINAIRE, STEADY LIGHT INTEGR. LED, AC/DC 24V, RED



Figure similar

General technical data:	
Product designation	Continuous light element
Type of voltage	AC/DC
• of the operating voltage	
Operating voltage	
• 1 at DC rated value	
• 1 at AC at 50 Hz rated value	
• 1 at AC at 60 Hz rated value	
Equipment marking	P
• acc. to DIN EN 81346-2	
Mechanical data:	
Product component Light source	Yes
Mounting type	Bayonet
Outer diameter of the signal column element	75 mm
Lamp:	
Design of the optical signal	continous light

Type of light source	LED
----------------------	-----

Ambient conditions:

Ambient temperature during operation	-20 ... +50 °C
Protection class IP	IP65
Depth	31 mm
Height	66 mm
Width	75 mm

Certificates/approvals

General Product Approval	EMC	Declaration of Conformity	other
--------------------------	-----	---------------------------	-------



[Confirmation](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/industrial-controls/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WD5320-5AB>

Cax online generator



<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=8WD5320-5AB>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/8WD5320-5AB>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=8WD5320-5AB&lang=en



SIEMENS

last modified:

06/05/2017