



1.783

MLFB-Ordering data : 2KJ3103-1AA05-0AW1-Z
D05+K06+L02+L50+Y00
{Y00:*ANL@0.37*}*AND@1800*}

Client order no. :

Order no. :

Offer no. :

Remarks :

Item no. :

Consignment no. :

Project :

Gearbox	
Type designation	SIMOGEAR Z39-K5-(56)
Gearbox	Helical gearbox Z39
Mounting type gearbox	Foot-mounted design
Output shaft	V25 x 50 mm (Solid shaft with feather key)
Mounting position	(D05) M5
Transmission ratio	43.68 (1092 / 25)
Nominal torque	200.00 Nm
Output speed	41.209 rpm
Output torque	85.75 Nm
Service factor	2.33
Gear oil	(K06) Mineral oil CLP VG220
Oil charge	0.8 l
Specification	CE (Europe / other countries)
Environment temperature	-15 ... +40 °C
Weight without oil	0.2 kg
Housing material first gearbox	Aluminum

Gearbox options	
Output shaft bearing	Standard bearing
Output shaft sealing	Standard sealing
Gearbox breather	Pressure breather valve
Oil level control	Oil level screw
Oil drain	Oil drain plug

Adapter	
Adapter	K5 Short adapter for NEMA motors
Hole circle	5.87"
Centering	4.5"
Motor shaft	0.625" x 2.06"
Input speed (Info)	1800 rpm
Input power (Info)	0.37 kW
Input torque	2.0 Nm
Max. perm. input torque for continuous duty T1perm	5.0 Nm
Max. perm. input torque for short-time duty	12.5 Nm
Max. perm. input speed	4,500.0 rpm

Adapter options	
	-

General options	
Surface treatments	Painted
Coating	(L02) Coating for normal environmental stress C1
RAL Color	(L50) 5015 sky blue
Coating on flange	-
Packing	Standard packing
Liability for defects	12 months from date of delivery (standard)

Further information	
General product information	SIMOGEAR
Configurator	2KJ.....
Operating instructions	
Gearbox	BA 2030
Adapter	BA 2039
Catalog	MD 50.11 Gearboxes with adapter