



Rigid/IMC Conduit Fittings

T&B Catalog Number:

UPC Number: 129
Status: 78621000129
Description: Active

3 in. Malleable Iron Bushing. For use with Rigid/IMC Conduit.

Features

Smoothly rounded shoulder covers end of conduit; broad flange covers knockout hole.

High ribs make tightening easy with fingers or with wrench.

Locknut-type base gives improved bonding and resist loosening under conditions of vibration.

Application

For use with rigid/IMC conduits

General

Trade Size (inches) 3
Material Malleable Iron

Dimension Information

Dimension A (inches) 3 27/32
Dimension B (inches) 13/16

Specifications

3dmodel Available on Website

Packaging

T&B Inner Pack 5
Package in Units 25
T&B Sold in UOM Each
T&B Weight Per UOM 52 lbs. per 100

Application Support

T&B Sales Drawings wsd-000019

Notes

Availabe with DURA-PLATE Finish

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
 E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com