



T&B®

Liquidtight Flexible Cord & Cable Fittings

T&B Catalog Number:

2631

UPC Number:

78621002631

Status:

Active

Description:

1/2 in. straight Chase liquidtight steel cord connector, cord range-.125-.250.

Application

Suitable for use in hazardous locations in Class I, Div. 2; Class II, Div 1 & 2; Class III, Div 1 & 2, where general purpose equipment is specifically permitted by NEC 500-2(a).

Meets Coast Guard CG293

General

Material Steel

Dimension Information

Hub Size (inches)	1/2
Dimension A (inches)	1 1/16
Dimension B (inches)	1 3/16
Cord Range (inches)	.125-.250

Specifications

3dmodel	Available on Website
Temperature Rating	105 C

Packaging

T&B Inner Pack	25
Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	20.1 lbs. per 100

Application Support

Product Overview	Available on Website
Portable Cord Selection Table	Available on Website

Notes

Suitable for use in hazardous locations in Class I, Div. 2; Class II, Div 1 & 2; Class III, Div 1 & 2, where general purpose equipment is specifically permitted by NEC 500-2(a).

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:

E 13938