



Liquidtight Flexible Cord & Cable Fittings

T&B Catalog Number:

UPC Number: 2632
 Status: 78621002632
 Description: Active

1/2 in. straight Chase liquidtight steel cord connector, cord range-.250-.375.

Application

Suitable for use in hazardous locations in Class I, Div. 2; Class II, Div 1 & 2; Class III, Div 1 & 2, where general purpose equipment is specifically permitted by NEC 500-2(a).
 Meets Coast Guard CG293

General

Material Steel

Dimension Information

Hub Size (inches) 1/2
 Dimension A (inches) 1 1/16
 Dimension B (inches) 1 3/16
 Cord Range (inches) .250-.375

Specifications

3dmodel Available on Website
 Temperature Rating 105 C

Packaging

T&B Inner Pack 25
 Package in Units 50
 T&B Sold in UOM Each
 T&B Weight Per UOM 19.5 lbs. per 100

Application Support

Product Overview Available on Website
 Portable Cord Selection Table Available on Website

Notes

Suitable for use in hazardous locations in Class I, Div. 2; Class II, Div 1 & 2; Class III, Div 1 & 2, where general purpose equipment is specifically permitted by NEC 500-2(a).

Certifications

RoHS Compliance Yes

Certifications



File Nbr:
 E 13938