



## Type A-Non-Metallic Liquidtight Conduit & Fittings

### T&B Catalog Number:

**UPC Number:** 3726  
**Status:** 78621003726  
**Description:** Active

2 Inch malleable iron Type A straight liquidtight connector with insulated throat and sealing ring with steel retainer.

#### Features

Steel or malleable iron construction with nylon-insulated throat  
 Santoprene sealing gasket includes Type 316 stainless steel retaining ring.  
 NPT hub threads seal in female threads.  
 Offers high mechanical pull-out strength.  
 Supplied with sealing ring and steel locknut.  
 Available in straight, 45 degree and 90 degree in hub sizes from 3/8 in. to 2 in..

#### Application

Provides a positive seal against water, oil and dust.

#### General

Trade Size (inches) 2  
 Material Malleable Iron

#### Dimension Information

Dimension A (inches) 3 17/32  
 Dimension B (inches) 3 5/8

#### Specifications

3dmodel Available on Website

#### Packaging

T&B Inner Pack 1  
 Package in Units 5  
 T&B Sold in UOM Each  
 T&B Weight Per UOM 242 lbs. per 100

#### Application Support

Product Brochure-Type A Liquidtight Con- Available on Website  
 nectors & Conduit  
 Product Overview-Type A Liquidtight Flex-Available on Website  
 ible Metal Conduit & Connectors  
 Guide to Nonmetallic Conduit Applications Available on Website

#### Notes

Santoprene is a registered trademark of Advanced Elastomer Systems.

#### Certifications

RoHS Compliance Yes

## Certifications



File Nbr:  
E 23018

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)