



Rigid/IMC Conduit Fittings

T&B Catalog Number:

3889

UPC Number:

78621003889

Status:

Active

Description:

2 in. Threaded insulated Grounding Bushing, Aluminum-Electro Zinc Plated, wire range-8-2/0, thermoplastic insulator. For use with Rigid/IMC Conduit.

Application

For quick installation of bonding jumper to multiple metal conduits (Rigid and IMC).

Designed to bush conductors and prevent insulation damage.

General

Trade Size (inches)	2
Material	Malleable Iron
Finish	Electro Zinc Plated
Wire Range	8-2/0

Dimension Information

Bushing Diameter (inches)	3.031
Throat Diameter (inches)	1.86
Lug Length (inches)	1.675
Swing Radius (inches)	2.355
Bushing Height (inches)	0.77
Conduit Size (inches)	2

Specifications

3dmodel	Available on Website
---------	----------------------

Packaging

T&B Inner Pack	5
Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	42.81 lbs. per 100

Application Support

T&B Instruction Sheets	ta00375-tb2
------------------------	-------------

Notes

Available with DURA-PLATE Finish

Certifications

RoHS Compliance	No
-----------------	----

Certifications



File Nbr:

E 3060

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125

T&B Technical Support
MS 3B-50
8155 T&B Blvd.

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289