



Project: Punta Catalina
Location: Dominican Republic
Anxter

Rigid/IMC Conduit Fittings

T&B Catalog Number:

UPC Number: 3996
78621003996
Status: Active
Description:

4 in. Threaded insulated Grounding Bushing, Aluminum-Electro Zinc Plated, wire range-6-4/0, thermoplastic insulator. For use with Rigid/IMC Conduit.

Application

For quick installation of bonding jumper to multiple metal conduits (Rigid and IMC).

Designed to bush conductors and prevent insulation damage.

General

Trade Size (inches)	4
Material	Malleable Iron
Finish	Electro Zinc Plated
Wire Range	6-4/0

Dimension Information

Bushing Diameter (inches)	5.328
Throat Diameter (inches)	3.623
Lug Length (inches)	2.23
Swing Radius (inches)	3.834
Bushing Height (inches)	0.98
Conduit Size (inches)	4

Specifications

3dmodel	Available on Website
---------	----------------------

Packaging

Package in Units	5
T&B Sold in UOM	Each
T&B Weight Per UOM	125 lbs. per 100

Application Support

T&B Instruction Sheets	ta00375-tb2
------------------------	-------------

Notes

Availabe with DURA-PLATE Finish

Certifications

RoHS Compliance	No
-----------------	----