



Liquidtight Flexible Metal Conduit Fittings

T&B Catalog Number:

UPC Number:

5239GR

Status:

78621089612

Description:

Active

3 Inch external bonding liquidtight, flexible metal conduit connector, straight, with Copper lug for #2-4/0 ground wire, for use in wet locations, non-insulated

Features

Ability to install quickly with low torque effort

Application

To positively bond conduit to box or enclosure

General

Trade Size (inches)

3

Material

Steel

Finish

Electro Zinc Plated/Chromate Coating

Ground Wire

2-4/0

Dimension Information

Dimension A (inches)

5 3/16

Dimension B (inches)

4 1/4

Dimension C (inches)

1

Specifications

3dmodel

Available on Website

Packaging

Package in Units

1

T&B Sold in UOM

Each

T&B Weight Per UOM

510 lbs. per 100

Certifications

RoHS Compliance

No

Certifications



File Nbr:

E 3060

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com