

**Liquidtight Flexible Metal Conduit Fittings**
T&B Catalog Number:**UPC Number:**

5253AL

Status:

78621080255

Description:

Active

3/4 Inch 90 degree aluminum liquidtight connector. Non-insulated

Application

High-quality, corrosion-resistant, liquidtight termination for LTA flexible aluminum conduit.

General

Style	Non-Insulated
Trade Size (inches)	3/4
Material	Aluminum
Finish	Zinc Plating/Clear Chromate

Dimension Information

Dimension A (inches)	1 21/32
Dimension B (inches)	1 3/4
Dimension C (inches)	9/16

Specifications

3dmodel	Available on Website
---------	----------------------

Packaging

T&B Inner Pack	10
Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	17.31 lbs. per 100

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications

File Nbr:

E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com