

**Liquidtight Flexible Metal Conduit Fittings****T&B Catalog Number:**

5261

UPC Number:

78621005261

Status:

Active

Description:

3/8 Inch liquidtight sealing gasket with 316 stainless steel retainer and santoprene sealing material.

Features

Design locks resilient sealing material in steel.

Steel retainer protects seal from extruding out under torque and limits compression to an optimum predetermined value; provides high quality seal.

Resilient material flows and seals rough edges.

Application

When used with an externally threaded connector provides a tight seal against oil, fumes or moisture at the knockout opening.

General**Trade Size (inches)**

3/8

Material

Stainless Steel

Dimension Information**Dimension A (inches)**

0.95

Dimension B (inches)

0.11

Specifications**3dmodel**

Available on Website

Packaging**T&B Inner Pack**

50

Package in Units

100

T&B Sold in UOM

Each

T&B Weight Per UOM

5.63 lbs. per 1000

Certifications**RoHS Compliance**

No

Certifications**File Nbr:**

E 13938

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com