



Liquidtight Flexible Metal Conduit Fittings

T&B Catalog Number:

UPC Number:

5332GR

Status:

78621089998

Description:

Active

1/2 Inch external bonding liquidtight, flexible metal conduit, straight, insulated, with Revolver? Lug, with Tin Plated CU Alloy lug for #14-#4 ground wire, for use in wet locations, 25 pieces

Features

Ability to install quickly with low torque effort

Application

To positively bond conduit to box or enclosure

General

Trade Size (inches)	1/2
Material	Steel
Finish	Electro Zinc Plated/Chromate Coating
Ground Wire	14-8

Dimension Information

Dimension A (inches)	1 3/8
Dimension B (inches)	1 9/16
Dimension C (inches)	9/16

Specifications

3dmodel	Available on Website
---------	----------------------

Packaging

T&B Inner Pack	25
Package in Units	100
T&B Sold in UOM	Each
T&B Weight Per UOM	19.81 lbs. per 100

Certifications

RoHS Compliance	Yes
-----------------	-----

Certifications



File Nbr:

E 3060

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com