



## Liquidtight Flexible Metal Conduit Fittings

T&B Catalog Number:

UPC Number: 5345  
Status: 78621005345  
Description: Active

1-1/4 Inch 45 Degree Malleable Iron Insulated Liquidtight Connector

### Features

Ability to install quickly with low torque effort

### Application

Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.

To positively bond conduit to box or enclosure.

### General

|                     |                                      |
|---------------------|--------------------------------------|
| Style               | Insulated                            |
| Trade Size (inches) | 1 1/4                                |
| Material            | Malleable Iron                       |
| Finish              | Electro Zinc Plated/Chromate Coating |

### Dimension Information

|                      |        |
|----------------------|--------|
| Dimension A (inches) | 2 9/32 |
| Dimension B (inches) | 2 3/4  |
| Dimension C (inches) | 13/16  |

### Specifications

|         |                      |
|---------|----------------------|
| 3dmodel | Available on Website |
|---------|----------------------|

### Accessories & Components

|                                         |         |
|-----------------------------------------|---------|
| Wiremesh Grips for Liquidtight Fittings | WMG-LT5 |
|-----------------------------------------|---------|

### Packaging

|                    |                 |
|--------------------|-----------------|
| T&B Inner Pack     | 5               |
| Package in Units   | 25              |
| T&B Sold in UOM    | Each            |
| T&B Weight Per UOM | 98 lbs. per 100 |

### Certifications

|                 |     |
|-----------------|-----|
| RoHS Compliance | Yes |
|-----------------|-----|

### Certifications



File Nbr:  
E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289

[www.tnb.com](http://www.tnb.com)

Memphis, TN 38125

Fax: (901) 252-1321

Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)