



Liquidtight Flexible Metal Conduit Fittings

T&B Catalog Number:

UPC Number:

5350GR

Status:

78621089634

Description:

Active

4 Inch 45 degree malleable iron external bonding liquidtight insulated connector.

Features

Ability to install quickly with low torque effort

Application

To positively bond conduit to box or enclosure

General

Trade Size (inches)	4
Material	Malleable Iron
Finish	Electro Zinc Plated/Chromate Coating
Ground Wire	2-4/0

Dimension Information

Dimension A (inches)	6 1/8
Dimension B (inches)	4 5/8
Dimension C (inches)	1 1/8

Specifications

3dmodel	Available on Website
---------	----------------------

Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	1240 lbs. per 100

Certifications

RoHS Compliance	No
-----------------	----

Certifications



File Nbr:

E 3060

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com