




H-118 Lock Washer

Cat. No.	Sizes (in.)	Wt. lbs./C
H-118-A	1/4	.259
H-118-B	5/16	.550
H-118-C	3/8	.630
H-118-D	1/2	1.436
H-118-E	5/8	2.587
H-118-F	3/4	4.293

Standard finish: Galv-Kröm unless otherwise specified.



H-119 Square Washer

Cat. No.	Dimensions (in.)		Wt. lbs./C
	Size	Thickness	
H-119-A	1/4	1/8	8.10
H-119-B	5/16	1/8	8.00
H-119-C	3/8	3/16	11.50
H-119-D	1/2	1/4	14.36
H-119-E	5/8	1/4	13.50
H-119-F	3/4	1/4	12.50
H-119-G	7/8	1/4	13.00

Standard finish: Galv-Kröm unless otherwise specified.




For rigid attachment of rod to channel. For use with either 3/8" or 1/2" hanger rod.

H-120 Saddle Type Washer

Cat. No.	Wt. lbs./C
H-120	7

Standard finish: Galv-Kröm unless otherwise specified.




A 5/8"-18 x 2" galvanized steel nipple in assembly with four jam nuts. This feed attachment provides spacing between lighting fixtures and raceway channels.

H-133-N Nipple Assembly

Cat. No.	Wt. lbs./C
H-133-N	27

Approved for G.S.A. installations.



Used for attaching fixture to channel with a uniform 1" clearance between fixture and supporting channel. Assembly includes a 1" spacer, a 5/8"-18 x 1 1/2" bolt and jam nut, all galvanized.

H-134-S Spacer Assembly

Cat. No.	Wt. lbs./C
H-134-S	21

Approved for G.S.A. installations.