

Ocal®

Conduit Fittings-PVC Coated T&B Catalog Number:

UPC Number: HUB4-G
70450838885
Status: Active
Description:

4 Dark Gray PVC Coated Hub Connector, Zinc with thermoplastic insulating throat, sealing ring-Nitrile (BUNA N).

Features

Coated with a nominal .002 in. (2 mil) blue urethane on the interior, before PVC Coating is applied.
A minimum .040 in. (40 mil) PVC Coating is bonded to the exterior.
Innovative sealing ring and groove.
Hexagonal body and locknut design.
Insulated throat and sharper and deeper teeth.
Pressure sealing sleeves to protect the connection.

General

Custom_Finish	hub_4
Trade Size (inches)	4
Material	Zinc
Color	Dark Gray

Dimension Information

Dimension A (inches)	5 1/2
Dimension B (inches)	2 23/32
Dimension C (inches)	1 5/8
Dimension D (inches)	1/4
Dimension E (inches)	3 7/8

Technical Information

Chemical Resistance Chart	Available on Website
---------------------------	----------------------

Specifications

Ocal Specification Guide-1995 Master Format-PDF	Available on Website
Ocal Specification Guide-1995 Master Format-DOC	Available on Website
Ocal Specification Guide-2004 Master Format-PDF	Available on Website
Ocal Specification Guide-2004 Master Format-DOC	Available on Website

Packaging

Package in Units	4
T&B Sold in UOM	Each
T&B Weight Per UOM	4.65 lbs. Each

Application Support

Ocal PVC Coated Conduit System	Available on Website
Ocal Specifications	Available on Website

