



Type A-Non-Metallic Liquidtight Conduit & Fittings

T&B Catalog Number:

UPC Number: 6322
Status: 78621006322
Description: Active

1/2 Inch 90 Degree Non-metallic Type A Liquidtight Connector With Cap-tive Sealing O-ring and Tapered Hub Thread

Features

	Serrated design provides high mechanical pull-out strength.
	Unique component parts (body/gland) design en-sures positive seal between conduit and connector.
	Tapered thread hub and furnished neoprene seal-ing O-ring provide a liquidtight, dust-tight seal to a box or enclosure.
	Smooth insulated body throughout for maximum di-electric strength.
	Captive O-ring and reduced number of parts save installation time.

Application

	To provide a liquidtight; dust tight connection be-tween flexible, non-metallic conduit and a box or an enclosure.
	Chemical resistant, ideal for corrosive environments
	Ideal for automotive and automotive OEM applica-tions, electric signs and outdoor lighting over 1000V (Article 600.31(A)), and pool and spa wiring. (Article 680)

General

Trade Size (inches)	1/2
Material	Thermoplastic

Dimension Information

Dimension A (inches)	0.6
Dimension B (inches)	1.56
Dimension C (inches)	1.48

Specifications

3dmodel	Available on Website
---------	----------------------

Packaging

T&B Inner Pack	10
Package in Units	50
T&B Sold in UOM	Each
T&B Weight Per UOM	13.5 lbs. per 100

Application Support

Product Brochure-Type A Liquidtight Con-nectors & Conduit

Available on Website

Product Overview-Type A Liquidtight Flex-
ible Metal Conduit & Connectors

Guide to Nonmetallic Conduit ApplicationsAvailable on Website

Certifications

RoHS Compliance Yes

Certifications



File Nbr:

E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com