




T&B®

Rigid/IMC Conduit Fittings-Hazardous Location

T&B Catalog Number:

UPC Number: GUP215-TB
Status: 78621096281
Description: Active

3/4 in. GUP Explosion-proof Junction Box, Body material and finish-Ductile Iron-Electro galvanized and aluminum acrylic paint; Cover material Copper-free Cast Aluminum; O-Ring-Neoprene. 6 hubs (NPT): 2-top, 2-bottom and 1-each side.

Features

Compact design
 O-ring gasket standard for raintight applications
 Supplied with 3 conduit plugs

Application

Junction for conduits in hazardous locations.

General

Material: Ductile Iron
 Finish: Electrogalvanized and Aluminum Acrylic Paint

Dimension Information

Hub Size (inches): 3/4

Specifications

3dmodel: Available on Website

Packaging

Package in Units: 1
 T&B Sold in UOM: Each
 T&B Weight Per UOM: 4.5 lbs. Each

Application Support

T&B Sales Drawings: wsd-000195

Notes

*Note: Class I Div 1 & 2, Groups C, D; Class II, Div 1 & 2, Groups E, F, G; Class III Rated; UL886 Listed; CSA Standard C22.2

Certifications

RoHS Compliance: Yes

For further technical assistance, please contact us...

Thomas & Betts - USA
 8155 T&B Blvd.
 Memphis, TN 38125
www.tnb.com

T&B Technical Support
 MS 3B-50
 8155 T&B Blvd.
 Memphis, TN 38125

Hours: 7AM - 6PM CDT
 Monday-Friday
 Phone: (888) 862-3289
 Fax: (901) 252-1321
 Email: techsupport@tnb.com