



Conduit Fittings-PVC Coated

T&B Catalog Number:

UPC Number:

LBY35-G

Status:

70450839228

Description:

Active

1 in. PVC coated gray, female to female service entrance elbow, material-malleable iron.

Features

A minimum of .040 in. (40 mil) PVC coating is bonded to the exterior.

Double coated with a nominal .002 in. (2 mil) blue urethane on both the interior and exterior, before PVC coating is applied.

Pressure-sealing sleeves protect the connections

Application

Installed in conduit systems to make 90 degree bends where space is limited

To provide access to conductors for maintenance and future system changes

General

Trade Size (inches)

1

Material

Malleable Iron

Finish

PVC Coated

Color

Gray

Dimension Information

Pipe Size (Metric Size Designator*)

27

Technical Information

Chemical Resistance Chart

Available on Website

Specifications

Ocal Specification Guide-1995 Master Format-PDF

Available on Website

Ocal Specification Guide-1995 Master Format-DOC

Available on Website

Ocal Specification Guide-2004 Master Format-PDF

Available on Website

Ocal Specification Guide-2004 Master Format-DOC

Available on Website

Packaging

Package in Units

15

T&B Sold in UOM

Each

T&B Weight Per UOM

2.04 lbs. Each

Application Support

Ocal Specifications

Available on Website

Recommended Installation Procedures

Available on Website

Product Overview-Conduit Outlet Bodies

Available on Website

NEMA Standards-RN 1

Available on Website

NEC 310-16 - Conductors for General Wiring

Available on Website

NEC Table 8

Available on Website

Notes

Dimensional values are of uncoated fittings.

Certifications

RoHS Compliance

Yes

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com