



T&B®

XTRAFLEX Liquidtight Conduit Tubing & Fittings

T&B Catalog Number:

UPC Number: LT125P
Status: 78621045068
Description: Active

1-1/4 in. non-metallic liquidtight Bullet.

Features

	Outside surface has friction reducing ridges.
	Inner surface teeth bite into conduit or tubing to enhance clamping and sealing action.
	Fitting ferrule designed to accept variations in conduit sizes and field conduit cuts.
	Smooth ferrule profile reduces friction to ensure a tight conduit-to-fitting seal.

Application

	T&B Bullet meets performance requirements when terminating Type B liquidtight non-metallic conduit or flexible non-metallic tubing to a box or enclosure with knockout opening or threaded hub.
	Suitable for hazardous locations; Class I Div 2; Class II Div 1 & 2; Groups E, F, G; Class III per N.E.C.; Article 501-4, 502-4 and 503-3

General

Trade Size (inches)	1 1/4
Material	Thermoplastic

Dimension Information

Dimension A (inches)	0.750
Dimension B (inches)	2.164
Dimension C (inches)	2.494
Dimension D-Minimum Throat (inches)	1.257
A (mm)	19.05
B (mm)	54.97
C (mm)	63.35
D (mm)	31.93

Specifications

3dmodel	Available on Website
---------	----------------------

Packaging

T&B Inner Pack	5
Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	33.8 lbs. per 100

Application Support

T&B Instruction Sheets	ta00998-tb2
Guide to Nonmetallic Conduit Applications	Available on Website
XTRAFLEX System Specifications	Available on Website