



Type B Liquidtight Conduit Tubing & Fittings

T&B Catalog Number:

UPC Number: LT9100P
Status: 78621045074
Description: Active

1 Inch 90 Degree Non-Metallic Liquidtight Bullet Connector

Features

	Outside surface has friction reducing ridges.
	Inner surface teeth bite into conduit or tubing to enhance clamping and sealing action.
	Fitting ferrule designed to accept variations in conduit sizes and field conduit cuts.
	Smooth ferrule profile reduces friction to ensure a tight conduit-to-fitting seal.

Application

	T&B Bullet meets performance requirements when terminating Type B liquidtight non-metallic conduit or flexible non-metallic tubing to a box or enclosure with knockout opening or threaded hub.
	Suitable for hazardous locations; Class I Div 2; Class II Div 1 & 2; Groups E, F, G; Class III per N.E.C.; Article 501-4, 502-4 and 503-3

General

Trade Size (inches)	1
Material	Thermoplastic

Dimension Information

Dimension A (inches)	0.726
Dimension B (inches)	2.104
Dimension C (inches)	2.068
Dimension D-Minimum Throat (inches)	0.94
Dimension F (inches)	2.508
A (mm)	18.44
B (mm)	53.44
C (mm)	52.53
D (mm)	23.88
F Approx. (mm)	63.7

Specifications

3dmodel	Available on Website
---------	----------------------

Packaging

T&B Inner Pack	5
Package in Units	25
T&B Sold in UOM	Each
T&B Weight Per UOM	25 lbs. per 100

Application Support

T&B Instruction Sheets	ta00970-tb2
------------------------	-------------

Guide to Nonmetallic Conduit Applications Available on Website

XTRAFLEX System Specifications Available on Website

Certifications

RoHS Compliance Yes

Certifications



File Nbr:

E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com