



Conduit Fittings-PVC Coated

T&B Catalog Number:

UPC Number: NPL3X6-G
Status: 70450840014
Description: Active

3 in. x 6 in. Dark Gray 40 mil PVC Coated Hot-Dip Galvanized Rigid Steel Conduit Nipple.

Features

A minimum .040 in. (40 mil) PVC coating on exterior.

A nominal .002 (2 mil) blue urethane on the interior. Color coded thread protectors on each end.

Blue urethane coating over threads.

General

Material Steel
Finish PVC Coated
Color Dark Gray

Dimension Information

Pipe Size (inches) 3
Pipe Size (Metric Size Designator*) 78
Length (inches) 6
Length (mm) 152.4

Technical Information

Chemical Resistance Chart Available on Website

Specifications

Ocal Specification Guide-1995 Master Format-PDF Available on Website
Ocal Specification Guide-1995 Master Format-DOC Available on Website
Ocal Specification Guide-2004 Master Format-PDF Available on Website
Ocal Specification Guide-2004 Master Format-DOC Available on Website

Packaging

Package in Units 8
T&B Sold in UOM Each
T&B Weight Per UOM 320 lbs. per 100

Application Support

Ocal Specifications Available on Website
Recommended Installation Procedures Available on Website
Product Overview-Conduit Outlet Bodies Available on Website
NEMA Standards-RN 1 Available on Website
NEC 310-16 - Conductors for General Wiring Available on Website
NEC Table 8 Available on Website

Notes

Metric size designator (ANSI C80. 1-1994)

Dimensions are of uncoated fittings.

Certifications

RoHS Compliance Yes

Certifications



File Nbr:

E 46453

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com