



Ocal[®]

Conduit Fittings-PVC Coated T&B Catalog Number:

UPC Number: NPL6X24-G
Status: 70450843111
Description: Active

6 in. x 24 in. Dark Gray 40 mil PVC Coated Hot-Dip Galvanized Rigid Steel Conduit Nipple

Features

	A minimum .040" (40 mil) PVC coating on exterior.
	A nominal .002 (2 mil) blue urethane on the interior.
	Color coded thread protectors on each end.
	Blue urethane coating over threads.

General

Material	Steel
Finish	Hot-Dip Galvanized
Color	Dark Gray

Technical Information

Chemical Resistance Chart	Available on Website
---------------------------	----------------------

Specifications

Ocal Specification Guide-1995 Master Format-PDF	Available on Website
Ocal Specification Guide-1995 Master Format-DOC	Available on Website
Ocal Specification Guide-2004 Master Format-PDF	Available on Website
Ocal Specification Guide-2004 Master Format-DOC	Available on Website

Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	1 lbs. Each

Application Support

Ocal PVC Coated Conduit System	Available on Website
Ocal Specifications	Available on Website
Recommended Installation Procedures	Available on Website
NEMA Standards-RN 1	Available on Website
NEC 310-16 - Conductors for General Wiring	Available on Website
NEC Table 8	Available on Website

Notes

	Metric size designator (ANSI C80. 1-1994)
	Dimensions are of uncoated fittings.

Certifications

RoHS Compliance	No
-----------------	----