



## Hazardous Location Fittings-PVC Coated

**T&B Catalog Number:**

EYS36-G

**UPC Number:**

70450837404

**Status:**

Active

**Description:**

1 in. Dark gray PVC coated, ductile iron male/female sealing fitting, vertical.

### Features

All hubs have a minimum of five full threads, integral bushings to protect conductor insulation from damage, and large access openings for easier packing of sealing material.

Seals are approved to be used with Crouse Hinds® Sealing Compound and Fiber.

### Application

Restricts the passage of gases, vapors and flames at atmospheric pressure and normal ambient temperatures

### General

|                     |              |
|---------------------|--------------|
| Trade Size (inches) | 1            |
| Material            | Ductile Iron |
| Finish              | PVC Coated   |
| Color               | Dark Gray    |

### Dimension Information

|                                     |      |
|-------------------------------------|------|
| Pipe Size (inches)                  | 1    |
| Pipe Size (Metric Size Designator*) | 27   |
| Hub Size (inches)                   | 1    |
| Dimension A (inches)                | 4.25 |
| Dimension B (inches)                | 1.75 |
| Dimension C (inches)                | 2.19 |
| Turning Radius (inches)             | 2.4  |

### Technical Information

|                           |                      |
|---------------------------|----------------------|
| Chemical Resistance Chart | Available on Website |
|---------------------------|----------------------|

### Specifications

|                                                 |                      |
|-------------------------------------------------|----------------------|
| Ocal Specification Guide-1995 Master Format-PDF | Available on Website |
| Ocal Specification Guide-1995 Master Format-DOC | Available on Website |
| Ocal Specification Guide-2004 Master Format-PDF | Available on Website |
| Ocal Specification Guide-2004 Master Format-DOC | Available on Website |

### Packaging

|                    |                |
|--------------------|----------------|
| Package in Units   | 10             |
| T&B Sold in UOM    | Each           |
| T&B Weight Per UOM | 2.32 lbs. Each |

### Application Support

|                                     |                      |
|-------------------------------------|----------------------|
| Ocal Specifications                 | Available on Website |
| Recommended Installation Procedures | Available on Website |

|                                            |                      |
|--------------------------------------------|----------------------|
| Product Overview-Conduit Outlet Bodies     | Available on Website |
| NEMA Standards-RN 1                        | Available on Website |
| NEC 310-16 - Conductors for General Wiring | Available on Website |
| NEC Table 8                                | Available on Website |

## Notes

Metric size designator (ANSI C80. 1-1994)  
Dimensions are of uncoated fittings

## Certifications

RoHS Compliance Yes

## Certifications



File Nbr:  
E 193396

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)