



Ocal[®]

Conduit Fittings-PVC Coated T&B Catalog Number:

UPC Number:
Status:
Description:

XJG88-G
70450841785
Active

3 in. Dark Gray PVC-Coated XJG Rigid Conduit Expansion Coupling with internal bonding jumper, Body-Malleable Iron-Zinc Plated; Internal Bonding Jumper-Tinned Copper Braid; Packing-PTFE/Synthetic Fiber Material, 8 in. movement.

Features

- No disassembly necessary to install
- True internal bonding jumper, no external grounding strap required
- Tamper-proof internal jumper protected from the environment
- Exceeds code requirements for long conduit runs to permit linear movement

Application

Allows for the contraction and expansion of a conduit run without reducing the mechanical or bonding integrity of the raceway.

General

Trade Size (inches)	3
Material	Malleable Iron
Color	Dark Gray

Dimension Information

Pipe Size (Metric Size Designator*)	78
Diameter (inches)	4.96
Length (inches)	16.12
Height (inches)	5.25
Movement (inches)	8

Technical Information


Chemical Resistance Chart	Available on Website
---------------------------	----------------------

Specifications

Ocal Specification Guide-1995 Master Format-PDF	Available on Website
Ocal Specification Guide-1995 Master Format-DOC	Available on Website
Ocal Specification Guide-2004 Master Format-PDF	Available on Website
Ocal Specification Guide-2004 Master Format-DOC	Available on Website

Packaging

Package in Units	1
T&B Sold in UOM	Each



T&B Weight Per UOM 15.9 lbs. Each

Application Support

Ocal PVC Coated Conduit System	Available on Website
Ocal Specifications	Available on Website
Recommended Installation Procedures	Available on Website
NEMA Standards-RN 1	Available on Website
NEC 310-16 - Conductors for General Wiring	Available on Website
NEC Table 8	Available on Website

Notes

Metric size designator (ANSI C80.1 - 1994)

Dimensions shown are for uncoated coupling.

Certifications



File Nbr:
E 23018

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com