

Ordinary Location Fittings — Liquidtight Fittings

The ultimate liquidtight solution for corrosive environments!

Ocal PVC-Coated Liquidtight Conduit Connectors



- Nominal .040" (40 mils) PVC coating bonded to exterior.
- Pressure-sealing sleeves are designated to protect the connection.
- Ocal™ uses only genuine T&B® liquidtight fittings to ensure quality installations

PVC-Coated Steel Straight Cat. No.	PVC-Coated Aluminum Straight Cat. No.	PVC-Coated Steel 45° Cat. No.	PVC-Coated Steel 90° Cat. No.	PVC-Coated Aluminum 90° Cat. No.	Pipe Size in. (mm)
ST3/8-	ST3/8SA-	ST3/845-	ST3/890-	ST3/890SA-	1/2 (16)
ST1/2-	ST1/2SA-	ST1/245-	ST1/290-	ST1/290SA-	3/4 (21)
ST3/4-	ST3/4SA-	ST3/445-	ST3/490-	ST3/490SA-	1 (27)
ST1-	ST1SA-	ST145-	ST190-	ST190SA-	1-1/4 (35)
ST1-1/4-	ST1-1/4SA-	ST1-1/445-	ST1-1/490-	ST1-1/490SA-	1-1/2 (41)
ST1-1/2-	ST1-1/2SA-	ST1-1/245-	ST1-1/290-	ST1-1/290SA-	2 (53)
ST2-	ST2SA-	ST245-	ST290-	ST290SA-	2-1/2 (63)
ST2-1/2-	ST2-1/2SA-	ST2-1/245-	ST2-1/290-	ST2-1/290SA-	3 (78)
ST3-	ST3SA-	ST345-	ST390-	ST390SA-	3-1/2 (91)
ST4-	ST4SA-	ST445-	ST490-	ST490SA-	4 (103)

Cat. No	Material	Colour
ST3/4		
	Blank = Steel/Iron	G = Grey
	SA = Aluminum	W = White
		B = Blue
		R = Red

Custom colours also available - Std. min. quantities are required.
Please contact your Regional Sales Office.