

Hazardous Location Fittings — PVC-Coated Sealing Fittings

OCAL-BLUE Double-Coat Sealing Fittings (continued)



EZS

EZS Series Sealing Fittings

Female Cat. No.	Male & Female Cat. No.	in. (mm)
EZS1-__	EZS16-__	1/2 (16)
EZS2-__	EZS26-__	3/4 (21)
EZS3-__	EZS36-__	1 (27)
EZS4-__	EZS46-__	1-1/4 (35)
EZS5-__	EZS56-__	1-1/2 (41)
EZS6-__	EZS66-__	2 (53)
EZS7-__	EZS76-__	2-1/2 (63)
EZS8-__	EZS86-__	3 (78)

Metric size designator (ANSI C80.1-1994).



EZD

EZD Series Sealing Fittings

Cat. No.	in. (mm)
EZD111-__	1/2 (16)
EZD211-__	3/4 (21)
EZD311-__	1 (27)
EZD411-__	1-1/4 (35)
EZD511-__	1-1/2 (41)
EZD611-__	2 (53)

Metric size designator (ANSI C80.1-1994).



EZD
with Inspection Cover off

Cat. No.	Colour
EYS1- __	__
__ = space for colour identifier	
G =	Grey
W =	White
B =	Blue

Custom colours also available - Std. min. quantities are required. Please contact your Regional Sales Office.

Ensures proper functioning of EYS sealing fittings.

Chico™ Sealing Compound and Fiber

- Sealing compound mixes with water, pours easily and hardens in 60 — 70 minutes.
- Fiber filler mineral wool holds sealing compound in place while it hardens.

OCAL-BLUE Double-Coat EYS Sealing Fittings require fiber filler and sealing compound to function properly. Use Chico™ X Fiber Filler to form a dam around the sealing fitting's integral bushing, as well as at the end of the conduit and around conductors entering the hub. Chico™ A Sealing Compound expands slightly while hardening and bonds to the inner walls of the sealing fitting.



FIBER-X6



SEAL-A3

Cat. No.	Description
SEAL-A3	Chico™ A Sealing Compound, 1 lb. net wt./23 cu.in. vol.
FIBER-X6	Chico™ X Fiber Filler, 8 oz.
SEALKIT-A4	Chico™ A Sealing Compound, 1 lb. net wt./23 cu.in. vol., with 1 oz. Chico® X Fiber Filler

Chico™ is a trademark of Cooper Technologies Company.