


Conduit and Cable

Conduit Supports



Features

- Available with Spring Steel Conduit Clip bottom mounted or side mounted
- Available for 3/8 in. through 2 in. trade sizes for EMT, rigid, flexible conduit and MC/AC cable
- Fits beam flanges 1/8 in. through 3/4 in. thick
- Will pivot through 360°
- Fig. 1 supports 75 lb. static load limit
- Fig. 2 supports 25 lb. static load limit
- Installs easily with a hammer and pliers




Fig. 1




Fig. 2



Cat. No. Fig. No. 1	Cat. No. Fig. No. 2	Description	Qty. Per Box
Flange Mount Conduit Clips			
SSF-CC3/8-H1/4	SSF-CC3/8-F1/4	14-2 thru 12-3 MC/AC cable and 3/8 in. conduits to 1/8 in. to 1/4 in. flanges and 3/8 in. conduits	25
SSF-CC1/2 3/4-H1/4	SSF-CC1/2 3/4-F1/4	1/2 in. conduit to 3/4 in. conduit to 1/8 in. to 1/4 in. flanges	
SSF-CC1-H1/4	SSF-CC1-F1/4	1 in. conduit to 1/8 in. to 1/4 in. flanges	
SSF-CC1 1/4-H1/4	SSF-CC1 1/4-F1/4	1-14 in. conduit to 1/8 in. to 1/4 in. flanges	
SSF-CC1 1/2-H1/4	SSF-CC1 1/2-F1/4	1-12 in. conduit to 1/8 in. to 1/4 in. flanges	
SSF-CC2-H1/4	SSF-CC2-F1/4	2 in. conduit to 1/8 in. to 1/4 in. flanges	
SSF-CC3/8-H1/2	SSF-CC3/8-F1/2	14-2 thru 12-3 MC/AC cable and 3/8 in. conduits to 5/16 in. to 1/2 in. flanges	
SSF-CC1/2 3/4-H1/2	SSF-CC1/2 3/4-F1/2	1/2 in. conduit to 3/4 in. conduit to 5/16 in. to 1/2 in. flanges	
SSF-CC1-H1/2	SSF-CC1-F1/2	1 in. conduit to 5/16 in. to 1/2 in. flanges	
SSF-CC1 1/4-H1/2	SSF-CC1 1/4-F1/2	1-14 in. conduit to 5/16 in. to 1/2 in. flanges	
SSF-CC1 1/2-H1/2	SSF-CC1 1/2-F1/2	1-12 in. conduit to 5/16 in. to 1/2 in. flanges	
SSF-CC2-H1/2	SSF-CC2-F1/2	2 in. conduit to 5/16 in. to 1/2 in. flanges	
SSF-CC3/8-H3/4	SSF-CC3/8-F3/4	4-2 thru 12-3 MC/AC cable and 3/8 in. conduits to 9/16 in. to 3/4 in. flanges	
SSF-CC1/2 3/4-H3/4	SSF-CC1/2 3/4-F3/4	1/2 in. conduit to 3/4 in. conduit to 9/16 in. to 3/4 in. flanges	
SSF-CC1-H3/4	SSF-CC1-F3/4	1 in. conduit to 9/16 in. to 3/4 in. flanges	
SSF-CC1 1/4-H3/4	SSF-CC1 1/4-F3/4	1-1/4 in. conduit to 9/16 in. to 3/4 in. flanges	
SSF-CC1 1/2-H3/4	SSF-CC1 1/2-F3/4	1-1/2 in. conduit to 9/16 in. to 3/4 in. flanges	
SSF-CC2-H3/4	SSF-CC2-F3/4	2 in. conduit to 9/16 in. to 3/4 in. flanges	

Features

- Available with Spring Steel Conduit Clip bottom mounted or side mounted
- Available for 1/2 in. through 1 in. EMT and rigid conduit
- Fits beam flanges 1/8 in. through 3/4 in. thick.
- Will pivot 360°
- Fig. 1 supports 25 lb. static load limit
- Fig. 2 supports 15 lb. static load limit
- Requires only hammer to install





Fig. 1




Fig. 2

Cat. No.	Fig. No.	Description	Static Load Limit	Qty. Per Box
Flange Mount Snap-in Conduit Clips				
SSF-CS1/2-H1/4	1	1/2 in. conduit to 1/8 in. to 1/4 in. flanges	25	25
SSF-CS3/4-H1/4	1	3/4 in. conduit to 1/8 in. to 1/4 in. flanges		
SSF-CS1-H1/4	1	1 in. conduit to 1/8 in. to 1/4 in. flanges		
SSF-CS1/2-H1/2	1	1/2 in. conduit to 5/16 in. to 1/2 in. flanges		
SSF-CS3/4-H1/2	1	3/4 in. conduit to 5/16 in. to 1/2 in. flanges		
SSF-CS1-H1/2	1	1 in. conduit to 5/16 in. to 1/2 in. flanges		
SSF-CS1/2-H3/4	1	1/2 in. conduit to 9/16 in. to 3/4 in. flanges		
SSF-CS3/4-H3/4	1	3/4 in. conduit to 9/16 in. to 3/4 in. flanges		
SSF-CS1-H3/4	1	1 in. conduit to 9/16 in. to 3/4 in. flanges	15	
SSF-CS1/2-F1/4	2	1/2 in. conduit to 1/8 in. to 1/4 in. flanges		
SSF-CS3/4-F1/4	2	3/4 in. conduit to 1/8 in. to 1/4 in. flanges		
SSF-CS1-F1/4	2	1 in. conduit to 1/8 in. to 1/4 in. flanges		
SSF-CS1/2-F1/2	2	1/2 in. conduit to 5/16 in. to 1/2 in. flanges		
SSF-CS3/4-F1/2	2	3/4 in. conduit to 5/16 in. to 1/2 in. flanges		
SSF-CS1-F1/2	2	1 in. conduit to 5/16 in. to 1/2 in. flanges		
SSF-CS1/2-F3/4	2	1/2 in. conduit to 9/16 in. to 3/4 in. flanges		
SSF-CS3/4-F3/4	2	3/4 in. conduit to 5/16 in. to 3/4 in. flanges		
SSF-CS1-F3/4	2	1 in. conduit to 5/16 in. to 3/4 in. flanges		