



Rigid/IMC Conduit Fittings

T&B Catalog Number:

UPC Number:

Status:

Description:

COND1/2SS

78620999311

Active

1/2 in. Type 304 Stainless steel conduit with type 316 stainless steel coupling.

Features

	Standard NPT threads for easy installation
	Exceeds requirements for wash down applications
	Also available in marine grade-Type 316 stainless steel
	Each 10 foot length of conduit ships with one Type 316 stainless steel conduit coupling
	Type 316 stainless steel couplings are sold separately
	Type 304 stainless steel offers up to five times the lifespan when compared to standard galvanized steel conduit in corrosive environments

Application

	Petrochemical refining and processing
	Water and wastewater treatment
	Food and beverage processing
	Marine and coastal facilities
	Pharmaceutical manufacturing
	Pulp and paper processing
	Corrosive environments

General

Material	Type 304 Stainless Steel
Color	Metallic

Dimension Information

Length (feet)	10
Size (inches)	1/2
Nominal Size (inches)	2-Jan
Nominal Size (mm)	16
Inside Diameter (inches)	0.622
Outside Diameter (inches)	0.84

Packaging

T&B Order Multiple	500
Package in Units	1500
T&B Sold in UOM	Feet
T&B Weight Per UOM	8.2 lbs. Each

Application Support

T&B Sales Drawings	wsd-001049
Product Brochure-Stainless Steel Conduit Available on Website	

Notes

10' length with coupling

Certifications



File Nbr:

Y

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com