


Rigid Conduit/IMC Fittings

Grounding Bushings — Die-Cast Zinc — Insulated with Aluminum Lay-In Type Lug

- For copper or aluminum bare ground wire
- 105° C thermoplastic liners
- Heavy reinforced ribs
- Three lug mounting positions



CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE CAPACITY	DIMENSIONS (IN.)		STD. CTN.
			A	B	
BG-801L	1/2	—	1 1/16	1/2	500
BG-802L	3/4	#14-#4 CU	1 1/4	1/2	500
BG-803L	1	or	1 9/16	5/8	250
BG-804L	1 1/4	#12-#4 AL	1 7/8	5/8	150
BG-805L	1 1/2	—	2 3/16	5/8	150
BG-806L	2	—	2 11/16	5/8	100

UL File No. E-3060.

CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE CAPACITY	DIMENSIONS (IN.)		STD. CTN.
			A	B	
BG-807L	2 1/2	#14-1/0 CU	3 3/4	7/8	60
BG-808L	3	or #12-1/0 AL	3 7/8	7/8	30
BG-809L	3 1/2	#6-250 kcmil	4 3/8	7/8	30
BG-810L	4	CU or AL	4 7/8	7/8	30

Grounding Bushings — Die-Cast Zinc — Insulated with Aluminum Lug

- For copper or aluminum bare ground wire
- 105° C thermoplastic liners
- Heavy reinforced ribs



CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE SIZE		STD. CTN.
		MIN.	MAX.	
BG-801A	1/2	14 AWG	6 AWG	500
BG-802A	3/4	14 AWG	6 AWG	500
BG-803A	1	14 AWG	6 AWG	250
BG-804A	1 1/4	14 AWG	2 AWG	200
BG-805A	1 1/2	14 AWG	2 AWG	100
BG-806A	2	14 AWG	2 AWG	100

UL File No. E-3060.

CAT. NO.	TRADE SIZE (IN.)	GROUNDING LUG WIRE SIZE		STD. CTN.
		MIN.	MAX.	
BG-807A	2 1/2	14 AWG	2/0 AWG	50
BG-808A	3	14 AWG	2/0 AWG	50
BG-809A	3 1/2	14 AWG	2/0 AWG	10
BG-810A	4	14 AWG	2/0 AWG	10
BG-810B	4	6 AWG	250 kcmil	10