



## Liquidtight Flexible Metal Conduit Fittings

T&B Catalog Number:

UPC Number: 5265  
78621005265  
Status: Active  
Description:

Liquidtight Sealing Gasket, 1-1/4 Inch, with 316 Stainless Steel Retainer and Santoprene Sealing Material

### Features

Design locks resilient sealing material in steel.  
Steel retainer protects seal from extruding out under torque and limits compression to an optimum predetermined value; provides high quality seal.  
Resilient material flows and seals rough edges.

### Application

When used with an externally threaded connector provides a tight seal against oil, fumes or moisture at the knockout opening.

### General

Trade Size (inches) 1 1/4  
Material Stainless Steel

### Dimension Information

Dimension A (inches) 2.15  
Dimension B (inches) 0.22

### Specifications

3dmodel Available on Website

### Packaging

T&B Inner Pack 5  
Package in Units 25  
T&B Sold in UOM Each  
T&B Weight Per UOM 2.5 lbs. per 100

### Application Support

T&B Sales Drawings wsd-001558

### Certifications

RoHS Compliance Yes

### Certifications



File Nbr:  
E 13938

For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.

T&B Technical Support  
MS 3B-50

Hours: 7AM - 6PM CDT  
Monday-Friday