



Liquidtight Flexible Metal Conduit Fittings

T&B Catalog Number:

5267

UPC Number:

78621005267

Status:

Active

Description:

Liquidtight Sealing Gasket, 2 Inch, with 316 Stainless Steel Retainer and Santoprene Sealing Material

Features

Design locks resilient sealing material in steel.

Steel retainer protects seal from extruding out under torque and limits compression to an optimum predetermined value; provides high quality seal.

Resilient material flows and seals rough edges.

Application

When used with an externally threaded connector provides a tight seal against oil, fumes or moisture at the knockout opening.

General

Trade Size (inches)

2

Material

Stainless Steel

Dimension Information

Dimension A (inches)

2.92

Dimension B (inches)

0.23

Specifications

3dmodel

Available on Website

Packaging

T&B Inner Pack

5

Package in Units

25

T&B Sold in UOM

Each

T&B Weight Per UOM

6.38 lbs. per 100

Application Support

T&B Sales Drawings

wsd-001558

Certifications

RoHS Compliance

Yes

Certifications



File Nbr:

E 13938

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.

T&B Technical Support
MS 3B-50

Hours: 7AM - 6PM CDT
Monday-Friday