





T&B Rigid Fittings




CONDUIT BODY IS SHOWN

NOTES:

1. MATERIAL:
BODY AND COVER: 316 STAINLESS STEEL
SCREWS AND WASHER RETAINERS: 18-8 STAINLESS STEEL
GASKET AND WASHER SEALS: SOLID NEOPRENE (-20°F TO 170°F)
2. FINISH:
COVER: MIRROR POLISHED
BODY: POLISHED
GASKET AND WASHER SEALS: BLACK IN COLOR
3. ALL DIMENSIONS ARE FOR REFERENCE ONLY.
4. ALL HUBS: NPT THREADS
5. SS CONDUIT BODIES AND COVERS ARE ASSEMBLED.
6. TWO SCREW COVER STYLE SHOWN. TRADE SIZES 1-1/2" & 2" SHALL HAVE (4) SCREW STYLE.
7. UL LISTED AND CSA CERTIFIED.



SS CONDUIT BODIES ARE ASSEMBLED AS SHOWN



T68SST	2" T STYLE CONDUIT BODY 88.0 CU IN; MAX. 3 WIRE 1/0	12.204"	3.820"	5.070"	2.900"	9.797"	9.125"
T58SST	1-1/2" T STYLE CONDUIT BODY 45.0 CU IN; MAX. 3 WIRE #1	10.046"	2.813"	3.867"	2.450"	7.938"	7.125"
T48SST	1-1/4" T STYLE CONDUIT BODY 24.0 CU IN; MAX. 3 WIRE #2	8.738"	2.200"	2.950"	2.200"	6.730"	5.810"
T38SST	1" T STYLE CONDUIT BODY 13.5 CU IN; MAX. 3 WIRE #4	7.500"	1.850"	2.850"	1.750"	5.625"	5.000"
T28SST	3/4" T STYLE CONDUIT BODY 9.0 CU IN; MAX. 3 WIRE #6	6.420"	1.645"	2.395"	1.400"	4.921"	4.300"
T18SST	1/2" T STYLE CONDUIT BODY 5.5 CU IN	5.820"	1.450"	2.200"	1.150"	4.320"	3.700"
CAT. NO.	TRADE SIZE ; VOLUME CONTENT; MAX. NUMBER & SIZE OF WIRES	DIM. "A"	DIM. "B"	DIM. "C"	DIM. "D"	DIM. "E"	DIM. "F"

GENERAL NOTES

1. ALL DIMENSIONS ARE FOR REFERENCE ONLY.
2. DIMENSIONS IN BRACKETS [] ARE IN METRIC UNITS.

REVISIONS

** SEE ERN (****)
FOR APPROVAL SIGNATURES
& RELEASE DATE.
PROJECT NO: ****

DESCRIPTION:

T STYLE ASSEMBLED SS CONDUIT BODIES

ORIGINAL PROJECT NO / (ERN NO)

RD55769 / (2012664)

SHEET NO:

1 OF 1

REV. NO:

1

DRAWING NO:

WSD-000529

Thomas & Betts
www.tnb.com

THIS DRAWING IS INTENDED FOR DESCRIPTIVE PURPOSES ONLY. AND THE RIGHT IS RESERVED TO DEViate FROM ANY OF THE DETAILS SHOWN HEREON.

© Thomas & Betts - Proprietary. All Rights Reserved