

3, 4 and 6-Wire Receptacles, Front Mount

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout
MFKS ..	MFKS 3-*		3x24 AWG, 105 °C, 125 V, 4 A, mates with 3-pin threaded female cordsets	Female 1. BN 3. BU 4. BK Male
		MFS 3-*	3x24 AWG, 105 °C, 125 V, 4 A, mates with 3-pin snap lock female cordsets	Male
	MFKS 4-*		4x24 AWG, 105 °C, 125 V, 4 A, mates with 4-pin threaded female cordsets	Female 1. BN 2. WH 3. BU 4. BK Male
		MFS 4-*	4x24 AWG, 105 °C, 125 V, 4 A, mates with 4-pin snap lock female cordsets	Male
	MFS ..	MFKS 6-*	6x24 AWG, 105 °C, 125 V, 2 A, mates with 6-pin threaded female cordsets	Female 1. BN 2. WH 3. BU 4. BK 5. GY 6. PK Male
		MFS 6-*	6x24 AWG, 105 °C, 125 V, 2 A, mates with 6-pin snap lock female cordsets	Male

* Length in meters. Standard lead length is 0.2 meters. Consult factory for other lengths.
Standard housing material is nickel plated brass .. "MFK(S).." ; "MFK(S)V.." indicates stainless steel.